Caravans 2024Technical Information

Valid from February 1st, 2024





Dethleffs Plus Factors –

Explanation of symbols

In the Dethleffs caravans, there are a lot of smart ideas and standard features for more safety and comfort. Here we present the most important ones with the corresponding symbols which can be found on the pages of the vehicle. More detailed information can be found at: www.dethleffs.com/plus-factors.

Family benefits



Happy family: Layouts with bunk beds – ideal for families. Up to three bunk beds available as an option.



Practical refrigerator with large volume and separate freezer compartment (details see technical data)

Added comfort



Inviting: 70 cm wide XXL entrance door



SleepWell: Fixed beds with 7-zone mattresses with ergonomic wooden slatted bed frames



More room: Fold-away lower bunk bed for more storage or greater playground (dep. on model)



Practical pull-down bed for easy stowage above the seating group (depending on model)



More legroom: One-leg telescopic table with easy lowering function for converting the lounge to bed (depending on model)

Added equipment



Winter expert! Winter-proof caravans thanks to optional Winter Comfort Packages (option)



Agile travelling – with caravans that go up to 100 km/h



For a healthy room climate: Optimum ventilation of the overhead lockers avoids condensation



System Information Unit: The SIU control unit incl. the sensors for displaying the vehicle leveling and the battery voltage are installed as standard (further sensors optionally available via Dethleffs Original Accessories)

Added safety



Vehicle roof made of robust GRP – protects from unusual weather conditions



Roof, front and rear made of robust GRP



Better safe than sorry: Benefit from Safety Packages for more safety on the road (option)



Safety on the road: Brand chassis from safety experts



Safety clutch: Stabilises rolling and pitching movements



Safety on the road: Thanks to the outstanding deceleration values and automated re-adjustment



Caravans 2024

	c′joy					c'go up		Aero			Aero up		Camper®	
	Single-axle	***************************************	Single-axle	••••••	•••••	Single-axle	•••••	Single-axle	•••••	••••••	Single-axle	•••••	Single-axle	
	Bunk bed	layouts Happing	<u> </u>	•			•••••		•••••	••••••	•			
								•						
	max. F	6 max.	6 P	max.		max.	max.	max. 6	max.	max.	max. 4	max. 4	6 P	max.
8 m								: : :						
6 m 5 m		() () () () () () () () () ()	(V-96				(100)	(V.00)					(V-846)	
Conversion length														
Conve	410 LK	480 QLK	495 QSK	565 FMK		465 KR	525 KR	470 FSK	490 QSK	500 QSK	460 KR	530 KR	500 QSK	530 FSK
Width	2,12 m	2,12 m	2,3 m	2,5 m		2,3 m	2,3 m	2,3 m	2,3 m	2,3 m	2,3 m	2,3 m	2,3 m	2,3 m
	Double be	ed layouts	•	••••••		:	•••••	• · · · · · · · · · · · · · · · · · · ·	•••••	•••••		•		
						9 9 9 9 9 9		•					• • • • • • • • • • • • • • • • • • •	
	max. T	max.	max.	max.	max. 4			max.	max.				0 0 0 0 0 0 0	
8 m														
6 m 5 m				(1000)										
length						* * * * * * * * * * * * * * * * * * *							• • • • • • • • • • • • • • • • • • •	
Conversion length													* * * * * * * * * * * * * * * * * * *	
Width	420 QSH 2,12 m	480 FSH 2,12 m	415 QL 2,2 m	475 FR 2,3 m	495 FR 2,3 m	0 0 0 0 0 0 0		410 QS 2,3 m	470 FR 2,3 m				0 0 0 0 0 0 0 0	
	Single bed	•••••	: -/- ···· 8	••••••			•••••	-/	•••••	•••••	: *	•••••		•••••••
		•••••	:	••••••		**************************************	••••	**************************************	•••••	•••••		***************************************	**************************************	
	max.		max.					max.	max.	max.	max.		max. 🛱	
8 m														
6 m									(1 ,000)		- (12/010)			
_ 5 m						•								
Conversion length						0 0 0 0 0 0 0 0 0								
Convers	460 LE		475 EL			- 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0		470 EL	510 ER	520 ER	530 ER		460 EL	
Width	2,12 m	••••	2,3 m	••••		•		2,3 m	2,3 m	2,3 m	2,3 m	••••	2,3 m	

Camper®		Nomad					:	Beduin Scandinavia					
Single-axle	Tandem- axle	Single-axle	•••••	•••••		Tandem- axle	Single-axle	•••••	Tandem-axle	e			
Bunk bed layouts		· <u>-</u>	•••••	••••	•••••	•		•••••	***************************************				
max.	max 8	6 P				max 8	max. F						
540 QMK 550 ESK 560 FM	730 FKR	560 FMK				730 FKR	540 QMK						
2,5 m 2,3 m 2,5 m	2,5 m	2,5 m	•••••	•••••	•••••	2,5 m	2,5 m	•••••		•••••••••••••••••••••••••••••••••••••••			
Double bed layouts		:	•••••	•••••	•••••	•••••	••••••••••••••••••••••••••••••••••••••	•••••					
		max. 4				max. 4	max.		max.				
		530 DR				650 RQT	550 RD		690 BQT				
			••••	••••	•	2,5 m	2,3 m	***************************************	2,5 m	•••••			
Single beds layouts		;	•••••	•••••	•••••	•••••	·····	•••••	·····				
(max. 17) 4		3 F	3 P	max 4	3 P		max. 2	max.		3 P			
510 LE 2,3 m		460 EL 2,3 m	490 EST 2,3 m	510 LE	520 ELT 2,5 m		550 BET 2,3 m	550 SE 2,3 m		670 BET			

IMPORTANT INFORMATION REGARDING THE SELECTION OF YOUR CARAVAN

When purchasing a caravan, it is especially important to select not only an appealing design, but also the right layout. Weight also plays an essential role here. Family, friends, optional equipment, accessories, and baggage – there should be enough space for all of this. At the same time, there are legal and technical limits for configuration and loading. Each caravan is designed for a certain weight which must not be exceeded during travel. This raises a question for caravan buyers: How should I configure my vehicle to accommodate baggage and accessories according to my needs without causing the vehicle to exceed this maximum weight? To help you make this decision, we have provided you some information below that is particularly important when selecting your vehicle from our product range:

1. The technically permissible maximum laden mass...

... is a value specified by the manufacturer which the vehicle must not exceed. Based on the layout, Dethleffs specifies an upper limit for the vehicle, which can vary from layout to layout (e.g. 1,600 kg, 1,700 kg). You will find the corresponding specification for each layout in the technical data.









	Caravans		460 EL	470 ER	470 FR	500 QSK
	Sleeping berths standard / max.		3	3	4	5/6 🔾
	Technically permissible maximum laden mass*	kg	1500	1500	1500	1500
	Manufacturer-specified mass for optional equipment*	kg	180	188	158	96
)	Mass in running order (± 5 %)*	kg	1235 (1173 to 1297)*	1225 (1164 to 1286)*	1245 (1183 to 1307)*	1295 (1130 to 1360)*

2. The mass in running order...

: - - - - - - - - - - - - - - - -

... consists – to put it simply – of the basic vehicle with standard equipment. It is legally permissible and possible for the mass in running order of your vehicle to deviate from the nominal value specified in the sales documents. The permissible tolerance is \pm 5%. The permissible range in kilograms is stated in parentheses after the mass in running order. In order to provide you with full transparency regarding possible weight deviations, Dethleffs weighs each vehicle at the end of the line and informs your trading partner of the weighing result of your vehicle for forwarding to you. For detailed explanations of the mass in running order and the effect of tolerances on the minimum payload and the payload , please refer to the "Legal notes" section.

3. The standard sleeping berths...

... are specified by the manufacturer and shown in the sales documents. The number of sleeping berths can be increased (e.g. 3-person bunk bed) or, if required, reduced (e.g. sideboard instead of seating group) by selecting optional equipment.









	Caravans		460 EL	470 ER	470 FR	500 QSK
)	Sleeping berths standard / max.		3	3	4	5/6 🔾
	Technically permissible maximum laden mass*	kg	1500	1500	1500	1500
)	Manufacturer-specified mass for optional equipment*	kg	180	188	158	96
	Mass in running order ((± 5 %) *	kg	1235 (1173 to 1297)*	1225 (1164 to 1286)*	1245 (1183 to 1307)*	1295 (1130 to 1360)*

4. The mass for optional equipment specified by the manufacturer...

... is a value set for each layout by Dethleffs for the maximum mass of optional equipment that can be ordered. This limit is intended to ensure that the minimum payload, i.e. the legally required free mass for baggage and retrofitted accessories, is actually available for the load capacity of the vehicles delivered by Dethleffs. If, in exceptional cases, the weighing at the end of the line nevertheless shows that the actual load capacity falls short of the minimum payload due to a permissible weight deviation, we will check together with your trading partner and you whether we should, for example, increase the load capacity of the vehicle or remove optional equipment before delivering the vehicle. For detailed explanations of the effects of the tolerances on the minimum payload and the payload, please refer to the "Legal notes" section.

Optional equipment*	Included in package	Price	Additional weight (kg)*	Code	460 EL	470 ER	470 FR
Bathroom							
Bathroom in alternative design	-	399,-	4	604	-	-	-
Multimedia							
Multifunctional external connection, 12 V, 220 V, TV and SAT	-	1.129,-	10	1049	-	0	0
Flat screen TV 22" incl. DVD player and receiver	-	999,-	3.5	1103	0	0	0
The street in 22 men 515 player and receive		,,,,	5.5	1103	O		O

5. The additional weight of optional equipment and packages...

... increases the actual mass of the vehicle (= mass in running order plus selected optional equipment) and reduces the payload. The specified value shows the additional weight compared to the standard equipment of the respective layout. The total weight of the selected packages and optional equipment must not exceed the mass for optional equipment specified by the manufacturer.



c'joy

Perfect for beginners

The c'joy has everything you need to experience great freedom. Thanks to its compact dimensions and low weight, it is also suitable for small cars and, depending on the towing vehicle, can also be driven with a class B driving licence. Nevertheless, it offers enough space - and that for up to 6 people - depending on the model. This makes holidays fun!

Technical info	
Overall length, approx.	622 - 714 cm
Overall width, approx.	212 cm
Overall height, approx.	265 cm
Headroom in living area, approx.	198 cm

Maximum values partly not possible for all models or only in connection with certain options.

Upholstery





+ Upholstery Timor

+ Upholstery Kapan

Wood décor



+ Wood décor Tindari Bora

O optionally available

Plus factors

- + Don't be afraid of narrow passages: with a width of just 212 cm, it is very easy to ride
- + Real lightweight: With the appropriate towing vehicle, a class B driving licence is often sufficient
- + Protects you from bad weather: roof, front and rear made of robust GRP
- + The perfect entry-level caravan: attractively priced and everything you need inside and out
- + You don't have to do without anything: The large storage compartments there is room for everything you need













c'joy Technical info











c'joy		410 LK	420 QSH	460 LE	480 FSH	480 QLK
Standard chassis		Lightweight chassis, 1100 kg	Lightweight chassis, 1100 kg	Lightweight chassis, 1200 kg	Lightweight chassis, 1200 kg	Lightweight chassis, 1200 kg
Overall length, approx.	cm	622	625	675	708	714
Body length approx.	cm	499	503	553	593	593
Overall width, approx.	cm	212	212	212	212	212
Overall height, approx.	cm	265	265	265	265	265
Circumferential dimension awning approx.	cm	914	918	968	1008	1008
Headroom in living area, approx.	cm	198	198	198	198	198
Thickness floor / side walls / roof	mm	38 / 28 / 28	38 / 28 / 28	38 / 28 / 28	38 / 28 / 28	38 / 28 / 28
Tire size		185 R14C 8PR	185 R14C 8PR	185 R14C 8PR	185 R14C 8PR	185 R14C 8PR
Bed dimension: Front bed, L x W, approx.	cm	190 x 140 - 115	195 x 150	190 x 100 - 90	200 x 160	190 x 150
Bed dimension: Central / middle bed, L X W, approx.	cm		170 x 90 - 80		170 x 90	190 x 120
Bed dimension: Rear bed, L x W, approx.	cm	190 x 65 / 190 x 70 / 2x 190 x 70 O / 190 x 60 O		200 x 80 / 195 x 80 / 200 - 195 x 190 O		190 x 60 / 190 x 70 / 2x 190 x 60 O / 190 x 70 O
Sleeping berths standard / max.		4/50	3	3	3	5/60
Mass in running order (+/-5%)*	kg	950 (903 to 998)*	920 (874 to 966)*	960 (912 to 1008)*	1025 (974 to 1076)*	1065 (1012 to 1118)*
$\label{eq:mass} \mbox{Manufacturer-specified mass for optional equipment}^*$	kg	60	100	155	86	126
Technically permissible maximum laden mass*	kg	1100	1100	1200	1200	1300
Heating		S 3004, 3.5 kW Gas	S 3004, 3.5 kW Gas	S 3004, 3.5 kW Gas	S 3004, 3.5 kW Gas	S 3004, 3.5 kW Gas
Refrigerator volume (thereof freezer), approx.	1	131,5 (15)	131,5 (15)	83 (8,2)	131,5 (15)	131,5 (15)
Fresh water tank capacity, total/ Fresh water tank capacity at dr filling	iving I	12 / 12	12 / 12	12 / 12	12 / 12	12 / 12
Sockets: 12 V / 230 V / USB		0/3/0	0/3/0	0/3/0	0/3/0	0/2/0

O Optional equipment ─ Not possible ● Standard equipment ◆ Mandatory △ Not known at the time of publication



The specified mass in running order is a standard value defined in the type approval procedure. Due to manufacturing tolerances, the actual weighed mass in running order may deviate from the value stated above. Deviations of up to \pm 5% of the mass in running order are legally permissible and possible. The permissible range in kilograms is stated in parentheses after the mass in running order. The mass for optional equipment specified by the manufacturer is an imputed value determined for each type and layout by which Dethleffs specifies the maximum weight available for factory-fitted optional equipment. The purpose of limiting optional equipment is to ensure that the minimum payload, i.e. the legally required free mass for baggage and retrofitted accessories, is actually available for the load capacity of vehicles delivered by

Standard equipment	410 LK	420 QSH	460 LE	480 FSH	480 QLK
Chassis					
Chassis galvanised, with overrun braking system and automatic reverse		•	•	•	
Tyres on steel wheels 185 R14 C 8 PR, up to and including 1.600 kg					
Chassis features					
High-quality brand-name tyres, designed for a speed of 100 km/h	•	•	•	•	•
Lightweight corner steadies	•	•	•	•	•
Exterior features					
Floor of the gas bottle locker made of rot-resistant and robust corrugated aluminium	•	•	•		
Front, rear and roof made of robust GRP	•				
Opening windows, insulated and double-glazed (graphite grey) with blackout and mosquito blinds	•	•	•	•	•
Storage space for 2 gas bottles with 11 kg filling weight each					•
Two-piece entrance door	•	•	•	•	•
Exterior design					
Sides in hammer finish, white	•	•	•	•	•
Access locker doors					
Access locker door rear right side 560x1150 mm	•	_	_	_	
Interior design					
Upholstery Timor					
Wood décor Tindari Bora		•	•	•	•
Textile equipment		Ď			
7-zones cold foam mattress single bed, left side, standard					
7-zones cold foam mattress single bed, right side, standard					
Cold foam double bed mattress	_		_		
Furniture layouts		Ň			
AirPlus - perfect air circulation in the interior and rear ventilation of the overhead lockers and sideboards					
Bunk bed with 2 sleeping berths, foldable				_	•
Bunk beds with safety net and ladder		_	_	_	•
Seating lounge converts to bed	•	•	•	•	•
Special slatted frame with flexible natural rubber holders, opening for optimal use of storage compartments under the beds					•
Kitchen					
Practical 3-flames cooker with manual ignition	•	•	•	•	•
Spacious fridge with 83 liters volume and 8.2 liters freezer compartment	_	_	•	_	_
Spacious refrigerator with 131.5 litre capacity and 15 litre freezer compartment	•		_		•
Bathroom					
Shapely washbasin	•	•	•	•	•
Shower tray	•	•	•	•	•
Skylight with mosquito net		•	•		•
Heating					
Gas heating S 3004 with automatic ignition	•	•	•	•	•
Electrical installation					
12 V power supply throughout vehicle	•	•	•	•	•
Awning light 12V	•	•	•	•	•
CEE external output socket for 230V on-board electrics					•
Compact power distribution unit with 230V safety device and 12V fuse box in wardrobe incl. powerful 340W transformer	•	•	•	•	•
Water supply					
Electric water supply	•	•	•	•	•
Fresh water canister 12 l	•				•
Miscellaneous					
SIU-ready (preparation for SIU control unit)	•	•	•	•	•

Packages c'joy

Package	Dynamic Package (13094)	Dynamic Package (13274)	Dynamic Package (13275)
Safety coupling	Х	Х	Х
Shock absorbers	Х	Х	х
Fresh water tank 44 l	Х	Х	х
Mobile 22 waste water tank	Х	Х	х
Spare wheel carrier in gas locker	Х	Х	х
Access locker door front right side 1000x420 mm	Х		
Access locker door rear right side 1000x420 mm		Х	
Access locker door front right side 750x300 mm			х
Additional weight (kg)*	28.1	28.1	28.1

Package	Autonomy Package I (10011)	Autonomy Package II (10012)
Battery (95 Ah)	X	Х
Battery charger	X	Х
Central 12V main switch	X	Х
Voltage display	Χ	Х
Fan 12V for S 3004	Χ	
Additional weight (kg)*	31	29

Touring Package (9243)

Hot water supply Hot air system Skylight 700 x 500 mm Flyscreen door

Additional weight (kg)*

13

 \triangle Not known at the time of publication



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the payload. The specified additional weight for packages and optional equipment shows the additional weight compared with the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the mass for optional equipment specified by the manufacturer in the model overviews. This is an imputed

Optional equipment*	Included in package	Additional weight (kg)*	Code	410 LK	420 QSH	460 LE	480 FSH	480 QLK
Chassis								
17" alloy wheels in Dethleffs design (single axle)	_	1	11608	0	0	0	0	0
Tyres on alloy wheels 185 R14 C LI102, up to and including 1600 kg	_	1	836	0	0	0	0	0
Weight upgrade								
Weight upgrade to 1.200 kg (without chassis change)	_	0	134	0	0	_	-	_
Weight upgrade to 1.300 kg (without chassis change)	-	0	135	_	0	_	_	_
Weight upgrade to 1.360 kg (without chassis change)	_	0	9619	0	0	0	0	0
Weight upgrade to 1.500 kg	-	20	136	_	0	=	_	_
Weight upgrade to 1.500 kg	_	0	136	_	_	_	0	0
Chassis features								
Draw bar cover	_	2.5	13098	0	0	0	0	0
ETS Plus stabilisation system	_	5.3	10764	0	0	0	0	0
Spare tyre with alloy wheel 185 R14 C LI 102, up to and including 1.600 kg	_	17	837	_	0	_	0	0
Spare tyre with alloy wheel 215/60 R17 C LI 109	_	24.1	11540	0	0	0	0	0
Spare tyre with steel wheel 185 R14 C 8 PR, up to and including 1.600 kg	_	18	831	_	0	_	0	0
Wheel trims for 14" tyres	_	0.5	276	0	0	0	0	0
Exterior features								
Flyscreen door	_	3	360	0	0	0	0	0
Front window	_	3	982		0		0	0
Kitchen window, sliding (change of window shape)	_	3	6406	0	0	0	0	0
Opening window in bathroom	_	2	1028	0	0	0	0	0
Rear window	_	4	1108	_	-	0	_	_
Skylight 700 x 500 mm	_	8	11575	0	0	0	0	0
Spare wheel carrier in gas locker	_	1	432	0	0	0	0	0
Access locker doors								
Access locker door front left side 1000x420 mm	_	2	6415	_	0	_	_	0
Access locker door front right side 1000x420 mm	_	2	6416	_	0	_	0	0
Access locker door front right side 750x300 mm	_	2	6420	0	_	_	_	_
Access locker door rear left side 1000x420 mm	_	2	6417	_	_	0	_	_
Access locker door rear right side 1000x420 mm	_	2	6418	_	_	0	_	
Interior design								
Upholstery Kapan	_	0	13226	0	0	0	0	0
Furniture layouts								
Bunk bed with 3 sleeping berths, not foldable	_	21	200	0	_	_	_	
Single beds convert to double bed	_	6	685	_	_	0	_	_
Multimedia				-				
	_	1	(11	0	_			
Multifunctional external connection, 12 V, 220 V, TV and SAT	_	1	611	0	0			
Preparation for flat screen TV (antenna cable and TV bracket)		2	678	0	0	0	0	0
Heating								
Fan 12V for \$ 3004		2	177	0	0	0	0	0
Hot air system	_	0	142	0	0	0	0	0
Ultraheat additional heating for S 3004, electric 220 V	_	2	364	0	0	0	0	0



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the payload. The specified additional weight for packages and optional equipment shows the additional weight compared with the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the mass for optional equipment specified by the manufacturer in the model overviews. This is an imputed

Optional equipment*	Included in package	Additional weight (kg)*	Code	410 LK	420 QSH	460 LE	480 FSH	480 QLK
Air Conditioning								
Pre-wiring for A/C	_	3.5	172	0	0	0	0	0
Electrical installation								
Additional lighting through LED spotlights	_	2	9692	0	0	0	0	0
USB port for spotlight bar	_	0.5	9989	0	0	0	0	0
Water supply								
Fresh water tank 44 l	_	6	9240	0	0	0	0	0
Hot water supply	_	2	123	0	0	0	0	0
Mobile 22 I waste water tank	_	3	367	0	0	0	0	0
Shower equipment with shower fittings and curtain		3	1097	0	0	0	0	0
Gas supply								
Gas detection system	_	0.5	10058	0	0	0	0	0
Packages								
Autonomy Package I ²⁾	_	31	10011	0	0	0	0	0
Autonomy Package II	_	29	10012	0	0	0	0	0
Dynamic Package ¹⁾	_	28.1	13094	_	0	_	0	0
Dynamic Package ¹⁾	_	28.1	13274	_	_	0	_	_
Dynamic Package ¹⁾	_	28.1	13275	0	_	_	_	_
Touring Package	_	13	9243	0	0	0	0	0
Miscellaneous								
Registration documents (CoC papers)	_	0	15151	*	•	*	•	*

O Optional equipment - Not possible lacktriangle Standard equipment lacktriangle Mandatory Δ Not known at the time of publication



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the payload. The specified additional weight for packages and optional equipment shows the additional weight compared with the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the mass for optional equipment specified by the manufacturer in the model overviews. This is an imputed

value determined for each model and layout that Dethleffs uses to determine the maximum weight available for factory-installed optional equipment. In the event of an increase of load capacity, the mass for optional equipment specified by the manufacturer is increased. For detailed information and explanations on the topic of weight, please refer to the "Legal notes" section.

c'go & c'go up

Caravans to go

The c'go makes you want to pack your bags and go on tour right away. Be inspired by the new and modern interior and feel at home, no matter where your journey takes you. In addition, the c'go has a wide choice of layouts: from the small compact to the spacious family caravan. Only the c'go up promises more freedom with its clever pull-down bed above the seating group, making it the ideal travel companion and particularly popular with young couples and small families. When do we leave?

Technical info	
Overall length, approx.	631 - 803 cm
Overall width, approx.	220 - 250 cm
Overall height, approx.	261 - 271 cm
Headroom in living area, approx.	198 - 208 cm

Maximum values partly not possible for all models or only in connection with certain options.

Upholstery







+ Upholstery Estepona O



+ Upholstery Manilva O

Plus factors

- + Lightweight: So light, in many cases you can even tow it with a class B driving licence (depending on the towing vehicle)
- + Something for everyone: thanks to the large selection of layouts
- + Protects you from bad weather: roof, front and rear made of robust GRP
- + Fresh look: chic, modern interior design and a stylish selection of upholstery to suit individual tastes
- + c'go up with standard fold-down bed (200 x 140 cm lying surface) above the seating group

























Wood décor



- + WEB Alaska White
- O optionally available

c'go & c'go up Technical info









c'go & c'go up		415 QL	475 EL	475 FR	495 FR
Standard chassis		Lightweight chassis, 1200 kg	Lightweight chassis, 1300 kg	Lightweight chassis, 1300 kg	Lightweight chassis, 1360 kg
Overall length, approx.	cm	631	676	680	725
Body length approx.	cm	498	552	558	588
Overall width, approx.	cm	220	230	230	230
Overall height, approx.	cm	261	261	261	261
Circumferential dimension awning approx.	cm	902	955	962	992
Headroom in living area, approx.	cm	198	198	198	198
Thickness floor / side walls / roof	mm	38 / 28 / 28	38 / 28 / 28	38 / 28 / 28	38 / 28 / 28
Tire size		185 R14C 8PR	185 R14C 8PR	185 R14C 8PR	185 R14C 8PR
Bed dimension: Front bed, L x W, approx.	cm	200 x 135	210 x 85 / 185 x 85 / 200 x 190 O	205 x 144 - 110	200 x 145 - 110
Bed dimension: Central / middle bed, L X W, approx.	cm				
Bed dimension: Rear bed, L x W, approx.	cm	200 x 130 - 100	210 x 105	212 x 132 - 149	210 x 150 - 130
Sleeping berths standard / max.		3	3	4	4
Mass in running order (+/-5%)*	kg	1005 (955 to 1055)*	1125 (1069 to 1181)*	1135 (1078 to 1192)*	1160 (1102 to 1218)*
Manufacturer-specified mass for optional equipment*	kg	115	90	69	101
Technically permissible maximum laden mass*	kg	1200	1300	1300	1360
Heating		S 3004, 3.5 kW Gas	S 3004, 3.5 kW Gas	S 3004, 3.5 kW Gas	S 3004, 3.5 kW Gas
Refrigerator volume (thereof freezer), approx.	1	78 (11)	78 (11)	137 (15)	137 (15)
Waste water tank, approx.	I	23	23	23	23
Fresh water tank capacity, total/ Fresh water tank capacity at filling	driving I	44 / 15	44 / 15	44 / 15	44 / 15
Sockets: 12 V / 230 V / USB		0 / 5 / 0	0 / 5 / 0	0 / 5 / 0	0 / 5 / 0



The specified mass in running order is a standard value defined in the type approval procedure. Due to manufacturing tolerances, the actual weighed mass in running order may deviate from the value stated above. Deviations of up to \pm 5% of the mass in running order are legally permissible and possible. The permissible range in kilograms is stated in parentheses after the mass in running order. The mass for optional equipment specified by the manufacturer is an imputed value determined for each type and layout by which Dethleffs specifies the maximum weight available for factory-fitted optional equipment. The purpose of limiting optional equipment is to ensure that the minimum payload, i.e. the legally required free mass for baggage and retrofitted accessories, is actually available for the load capacity of vehicles delivered by

c'go & c'go up Technical info









c'go & c'go up		495 QSK	565 FMK	up 465 KR	up 525 KR
Standard chassis		Lightweight chassis, 1360 kg	Lightweight chassis, 1600 kg	Lightweight chassis, 1500 kg	Lightweight chassis, 1600 kg
Overall length, approx.	cm	714	803	682	756
Body length approx.	cm	587	672	551	623
Overall width, approx.	cm	230	250	230	230
Overall height, approx.	cm	261	261	271	271
Circumferential dimension awning approx.	cm	990	1086	968	1040
Headroom in living area, approx.	cm	198	198	208	208
Thickness floor / side walls / roof	mm	38 / 28 / 28	38 / 28 / 28	38 / 28 / 28	38 / 28 / 28
Tire size		185 R14C 8PR	185 R14C 8PR	185 R14C 8PR	185 R14C 8PR
Bed dimension: Front bed, L x W, approx.	cm	210 x 135	205 x 165 - 130	2x 210 x 95	205 x 75 / 200 x 75 / 175 x 90 - 80
Bed dimension: Central / middle bed, L X W, approx.	cm	190 x 90	200 x 110		
Bed dimension: Rear bed, L x W, approx.	cm	2x 210 x 75 / 3x 210 x 75 O	2x 200 x 80 / 2x 200 x 80 O / 200 x 70 O	200 x 145 / 210 x 170 - 160	200 x 145 / 212 x 170 - 160
Sleeping berths standard / max.		5/60	5 / 6 🔿	6	7
Mass in running order (+/-5%)*	kg	1165 (1107 to 1223)*	1370 (1302 to 1439)*	1230 (1169 to 1292)*	1340 (1273 to 1407)*
Manufacturer-specified mass for optional equipment*	kg	86	113	155	128
Technically permissible maximum laden mass*	kg	1360	1600	1500	1600
Heating		S 3004, 3.5 kW Gas	S 5004, 6 kW Gas	S 3004, 3.5 kW Gas	S 3004, 3.5 kW Gas
Refrigerator volume (thereof freezer), approx.	1	137 (15)	137 (15)	137 (15)	137 (15)
Waste water tank, approx.	I	23	23	23	23
Fresh water tank capacity, total/ Fresh water tank capacity at filling	driving I	44 / 15	44 / 15	44 / 15	44 / 15
Sockets: 12 V / 230 V / USB		0/5/0	0/6/0	0/5/0	0/6/0

O Optional equipment ─ Not possible ● Standard equipment ◆ Mandatory △ Not known at the time of publication



The specified mass in running order is a standard value defined in the type approval procedure. Due to manufacturing tolerances, the actual weighed mass in running order may deviate from the value stated above. Deviations of up to \pm 5% of the mass in running order are legally permissible and possible. The permissible range in kilograms is stated in parentheses after the mass in running order. The mass for optional equipment specified by the manufacturer is an imputed value determined for each type and layout by which Dethleffs specifies the maximum weight available for factory-fitted optional equipment. The purpose of limiting optional equipment is to ensure that the minimum payload, i.e. the legally required free mass for baggage and retrofitted accessories, is actually available for the load capacity of vehicles delivered by

Standard equipment	415 QL	475 EL	475 FR	495 FR	495 QSK	565 FMK	up 465 KR	up 525 KR
Chassis	ü							
Tyres on steel wheels 185 R14 C 8 PR, up to and including 1.600 kg								
Zinc-plated chassis with inertia braking system with reversing automatic			•	•	•		•	
Chassis features								
AAA self-adjusting brake								
ACS stabiliser								
High-quality brand-name tyres, designed for a speed of 100 km/h								
Lightweight zinc-plated corner steadies								
Octagon shock absorber		•	•	•	•	•	•	•
Exterior features		Ĥ						
Floor of the gas bottle locker made of rot-resistant and robust corrugated aluminium								
Front, rear and roof made of robust GRP								
One-piece habitation door								
Opening windows, trapezoid, insulated and double-glazed (graphite grey) with blackout and mosquito blinds		_	•	•	•	•	•	
Skylight Mini Heki		_	•	•	•	•	•	
Spare wheel carrier in gas locker		•	•	•	•	•	•	
Storage space for 2 gas bottles with 11 kg filling weight each								
Exterior design								
Sides in hammer finish, white		•	•	•				
Access locker doors								
Access locker door front right side 1000x420 mm Access locker door front right side 749x297 mm								
Access locker door front right side 997x419 mm		_	_	_	_	_		
Interior design	-							
-			_	_	_			
Upholstery Ronda WEB Alaska White								
		Ť	Ť	Ť	Ť	Ť	Š	Ť
Textile equipment								
7-zones cold foam mattress single bed, left side, standard	_	•	_	_	_	_	_	
7-zones cold foam mattress single bed, right side, standard Cold foam double bed mattress								
		_	_	_		_	÷	i
Furniture layouts								
AirPlus - perfect air circulation in the interior and rear ventilation of the overhead lockers and sideboards	•	•	•	•		•	•	•
Bunk bed with 2 sleeping berths, foldable	_	_	_	_				
Bunk beds with safety net and ladder	_	_	_	_	•	•	•	
Seating lounge converts to bed Spacious pull-down bed above seating lounge, with manual control								
Special slatted frame with flexible natural rubber holders, opening for optimal use of storage compartments under the			_	_				
beds	•	•	•	•	•	•	•	•
Interior features								
Smoke detector					•			
Kitchen								
					^			
Generous drawers with soft closing for absolutely silent closing								
Large fridge with 137 liters capacity and 15 liters freezer compartment Practical 3-flames cooker with electric ignition								
Spacious fridge with 78 liters volume and 11 liters freezer compartment								
		Ť						
Bathroom								
Shapely washbasin		•	•	•	•			
Shower tray Skylight with masquite pot								
Skylight with mosquito net						Ť		
Heating								

Standard equipment	415 QL	475 EL	475 FR	495 FR	495 QSK	565 FMK	up 465 KR	up 525 KR
Gas heating S 3004 with automatic ignition	•	•	•	•	•	_	•	•
Gas heating S 5004 with automatic ignition	_	_	_	_	_		_	_
Electrical installation								
12 V power supply throughout vehicle	•	•	•	•	•	•	•	•
Additional lighting through LED spotlights	•	•		•	•	•		
Awning light 12V	•	•						
CEE external output socket for 230V on-board electrics	•	•						
Compact power distribution unit with 230V safety device and 12V fuse box in wardrobe incl. powerful 340W transformer	•							
LED spots in front and rear seating lounges		•		•	•	•		
Water supply								
Electric water supply	•	•	•	•	•	•	•	•
Fresh water tank 44 l	•							
Mobile 22 I waste water tank	•	•						
Miscellaneous								
Dethleffs Connect - System Information Unit: SIU control unit incl. voltage and levelling display via the Dethleffs app.	•	•	•	•	•	•	•	•

Packages c'go & c'go up

Package	Safety Package (9556)	Safety Package (9556)
ATC Trailer Control	Х	X
DuoControl safety gas pressure regulator with crash sensor	X	
DuoControl safety gas pressure regulator with crash sensor and EisEx gas regulator heater		х
Additional weight (kg)*	4.4	4.4

Package	Autonomy Package I (10011)	Autonomy Package II (10012)
Battery (95 Ah)	Х	X
Battery charger	X	Х
Central 12V main switch	Х	X
Voltage display	Х	Х
Fan 12V for S 3004	Х	
Additional weight (kg)*	31	29



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the payload. The specified additional weight for packages and optional equipment shows the additional weight compared with the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the mass for optional equipment specified by the manufacturer in the model overviews. This is an imputed

Package	Edition 10 Package 415 QL (14232)	Edition 10 Package 475 EL/FR (14232)	Edition 10 Package 495 FR (14232)	Edition 10 Package 495 QSK (14232)	Edition 10 Package 565 FMK (14232)	Edition 10 Package up 465 KR (14234)	Edition 10 Package up 525 KR (14236)
Draw bar cover	Х	Х	Х	х	Х	х	х
17" alloy wheels in Dethleffs design (single axle)	х	Х	Х	х	Х	х	х
Corner steadies incl. large-area support feet	Х	Х	Х	х	Х	х	х
Hot water supply	Х	Х	Х	х	Х	х	х
Flyscreen door	Х	Х	Х	х	Х	х	х
Hot air system	Х	Х	Х	х	Х	х	х
Heki II skylight incl. illuminated roof lining	х	х	х	х	х	х	х
Weight upgrade 1.700 kg (incl. steel wheel 195 R14 C L1106)	х						
Front window	х	Х	Х	х	Х		
Indirect lighting	х	Х	Х	х	Х	х	х
Shower equipment with shower fittings and curtain	х	Х	Х	х	Х	х	х
ATC Trailer Control	Х	Х	Х	х	Х	х	х
Smooth sides white	Х	Х				х	
Weight upgrade 1.700 kg (incl. steel wheel 195 R14 C L1106)		Х					
Smooth sides white			Х	х	Х		х
Weight upgrade 1.700 kg (incl. steel wheel 195 R14 C L1106)			х				
Weight upgrade 1.700 kg (incl. steel wheel 195 R14 C LI106)				х			
Weight upgrade 1.700 kg (incl. steel wheel 195 R14 C LI106)					Х		
Weight upgrade 1.700 kg (incl. steel wheel 195 R14 C LI106)						х	
Weight upgrade 1.800 kg (incl. steel wheel 195 R14 C L1106)							х
Additional weight (kg)*	65	86	94	66	56	55	55

Touring Package (7345)

Hot water supply

Hot air system

Flyscreen door

Heki II skylight incl. illuminated roof lining

Additional weight (kg)*

15

 \triangle Not known at the time of publication



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the payload. The specified additional weight for packages and optional equipment shows the additional weight compared with the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the mass for optional equipment specified by the manufacturer in the model overviews. This is an imputed

Optional equipment*	Included in package	Additional weight (kg)*	Code	415 QL	475 EL	475 FR	495 FR	495 QSK	565 FMK	up 465 KR	up 525 KR
Chassis											
17" alloy wheels in Dethleffs design (single axle)	ED	1	11608	0	0	0	0	0	0	0	0
Tyres on alloy wheels 185 R14 C LI102, up to and including 1600 kg	_	1	836	0	0			0	0	0	0
Tyres on alloy wheels 195 R14 C LI106, 1700 kg and 1800 kg		1	838	0	0	0	0	0	0	0	0
Weight upgrade											
Weight upgrade 1.700 kg (incl. steel wheel 195 R14 C LI106)	ED	15	278	0	_	_	_	_	_	_	_
Weight upgrade 1.700 kg (incl. steel wheel 195 R14 C LI106)	ED	36	278	_	0	0	_	_	_	_	_
Weight upgrade 1.700 kg (incl. steel wheel 195 R14 C LI106)	ED	6	278	_	_	_	_	_	0	_	_
Weight upgrade 1.700 kg (incl. steel wheel 195 R14 C LI106)	ED	8	278	_	_	_	_	_	_	0	_
Weight upgrade 1.700 kg (incl. steel wheel 195 R14 C LI106)	ED	44	278	_	_	_	0	_	_	_	_
Weight upgrade 1.700 kg (incl. steel wheel 195 R14 C LI106)	ED	16	278	_	_	_	_	0	_	_	_
Weight upgrade 1.800 kg (incl. steel wheel 195 R14 C LI106)	_	6	279	_	_	_	_	_	0	_	_
Weight upgrade 1.800 kg (incl. steel wheel 195 R14 C LI106)	ED	8	279	_	_	_	_	_	_	_	0
Weight upgrade 1.900 kg (incl. alloy wheel 225/70 R15 C LI112)	_	13	394	_	_	_	_	_	0	_	_
Weight upgrade 2.000 kg (incl. alloy wheel 225/70 R15 C LI112)	_	13	138	_	_	_	_	-	0	_	_
Weight upgrade to 1.300 kg	_	0	135	0	_	_	_	_	_	_	_
Weight upgrade to 1.360 kg (without chassis change)	_	0	9619	0	0	0	_	-	_	_	_
Weight upgrade to 1.400 kg	_	0	359	0	0	_	_	0	_	_	_
Weight upgrade to 1.400 kg	_	16	359	_	_	0	_	_	-	-	_
Weight upgrade to 1.400 kg	_	38	359	_	_	_	0	_	_	_	_
Weight upgrade to 1.500 kg	_	16	136	_	_	0	_	_	-	_	_
Weight upgrade to 1.500 kg	_	38	136	_	_	_	0	_	_	_	_
Weight upgrade to 1.500 kg	_	0	136	0	0	_	_	0	_	_	_
Chassis features											
ATC Trailer Control	ED	4	748	0	0	0	0	0	0	0	0
Corner steadies incl. large-area support feet	ED	4	9138	0	0	0	0	0	0	0	0
Draw bar cover	ED	2	434	0	0	0	0	0	0	0	0
Solid rubber support wheel with support load indicator	_	2	10063	0	0	0	0	0	0	0	0
Spare tyre with alloy wheel 185 R14 C LI 102, up to and including 1.600 kg	_	17	837	0	0	0	0	0	0	0	0
Spare tyre with alloy wheel 195 R14 C 8PR-LI 106, 1.700 kg and 1.800 kg	_	19	839	0	0	0	0	0	0	0	0
Spare tyre with alloy wheel 215/60 R17 C LI 109	_	24.1	11540	0	0	0	0	0	0	0	0
Spare tyre with steel wheel 185 R14 C 8 PR, up to and including 1.600 kg	_	18	831	0	0	0	0	0	0	0	0
Spare tyre with steel wheel 195 R14 C LI 106, 1.700 kg and 1.800 kg	_	20.4	833	0	0	0	0	0	0	0	0
Wheel trims for 14" tyres	_	0.5	276	0	0	0	0	0	0	0	0
Exterior features											
Flyscreen door	ED	3	360	0	0	0	0	0	0	0	0
Front window	ED	3	982	0	0	0	0	0	0	_	_
Heki II skylight incl. illuminated roof lining	ED	10	274	0	0	0	0	0	0	0	0
Kitchen window, sliding (change of window shape)	_	3	6406	0	0	0	0	0	0	0	0
One-piece habitation door with window	-	0	6427	-	=	-	Ξ	=	=	0	0



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the payload. The specified additional weight for packages and optional equipment shows the additional weight compared with the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the mass for optional equipment specified by the manufacturer in the model overviews. This is an imputed

Optional equipment*	Included in package	Additional weight (kg)*	Code	415 QL	475 EL	475 FR	495 FR	495 QSK	565 FMK	up 465 KR	up 525 KR
Opening window in bathroom	_	2	1028	0	0	0	0	0	0	0	0
Exterior design											
Smooth sides white	ED	17	443	0	0	0	_	_	_	0	_
Smooth sides white	ED	17	443	-	_	_	0	0	0	_	0
Access locker doors											
Access locker door front left side 1000x420 mm	_	2	6415	0	0	_	Ξ	0	•	_	_
Access locker door front right side 1675x885 mm	_	0	9430	_	_	_	_	_	_	_	0
Access locker door front right side 560x1150 mm	_	0	10393	_	_	_	=	_	_	0	_
Access locker door rear left side 749x297 mm	_	2	1077	_	_	_	_	_	_	_	0
Access locker door rear right side 749x297 mm	_	2	1078	_	_	=	=	_	=	0	0
Access locker door rear right side 750x300 mm	_	2	6422	0	_	0	0	_	_	_	_
Interior design											
Upholstery Estepona	_	0	13901	0	0	0	0	0	0	0	0
Upholstery Manilva	_	0	13902	0	0	0	0	0	0	0	0
Textile equipment											
7-zones mattress, made of heat-regulating material	_	0	10318	0	0	0	0	0	0	0	0
Loose carpet	_	7	513	0	0			0		0	0
Furniture layouts											
Bunk bed with 3 sleeping berths, not foldable	-	21	200	1-	-			0	0	_	_
Hanging table with rotating device	_	0	8699	_	_	_	_	0	_	_	_
Seat enlargement for opposite seating lounge (in comb. with option 8699) 3)	_	0	7750	_	_	_	_	0	_	_	_
Single beds convert to double bed	_	6	685	_	0	_	_	_	_	_	_
Multimedia											
Multifunctional external connection, 12 V, 220 V, TV and SAT ⁴⁾	_	1	611	0	0	0	0	0	0	0	0
Preparation for flat screen TV (antenna cable and TV bracket)	_	2	678	0	0	0	0	0	0	0	0
Heating											
Electric floor heating	_	6	387	0	0	0	0	0	0	0	0
Fan 12 V with automatic speed control for S 5004	_	2	178	_	_	_	_	_	0	_	_
Fan 12V for S 3004	_	2	177	0	0	0	0	0	_	0	0
Hot air system	ED	0	142	0	0	0	0	0	0	0	0
Ultraheat additional heating for S 3004, electric 220 V	_	2	364	0	0	0	0	0	_	0	0
Ultraheat additional heating for S 5004, electric 220 V	_	2	422	_	_	_	_	_	0	_	_
Air Conditioning											
Pre-wiring for A/C	_	3.5	172	0	0	0	0	0	0	0	0
Electrical installation											
Indirect lighting	ED	1	633	0	0	0	0	0	0	0	0
USB port for spotlight bar	_	0.5	9989	0	0	0	0	0	0	_	0



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the payload. The specified additional weight for packages and optional equipment shows the additional weight compared with the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the mass for optional equipment specified by the manufacturer in the model overviews. This is an imputed

Optional equipment*	Included in package	Additional weight (kg)*	Code	415 QL	475 EL	475 FR	495 FR	495 QSK	565 FMK	up 465 KR	up 525 KR
City water connection	_	2	414	_	_	_	_	_	_	0	0
Hot water supply	ED	2	123	0	0	0	0	0	0	0	0
Shower equipment with shower fittings and curtain	ED	3	1097	0	0	0	0	0	0	0	0
Gas supply											
DuoControl safety gas pressure regulator with crash sensor	_	0.4	784	0	0	0	0	0	0	0	0
DuoControl safety gas pressure regulator with crash sensor and EisEx gas regulator heater	_	2.5	784	_	_	_	_	_	_	0	0
Gas detection system	_	0.5	10058	0	0	0	0	0	0	0	0
Gas socket (exterior) 5)	_	1	187	0	0	0	0	0	0	0	0
Packages											
Autonomy Package I ⁶⁾	_	31	10011	0	0	0	0	0	0	0	0
Autonomy Package II	_	29	10012	0	0	0	0	0	0	0	0
Edition 10 Package 415 QL	_	65	14232	0	_	_	_	_	_	_	_
Edition 10 Package 475 EL/FR	_	86	14232	_	0	0	_	_	_	_	_
Edition 10 Package 495 FR	_	94	14232	_	_	_	0	_	_	_	_
Edition 10 Package 495 QSK	_	66	14232	_	_	-	_	0	_	-	_
Edition 10 Package 565 FMK	_	56	14232	_	_	_	_	_	0	_	_
Edition 10 Package up 465 KR	_	55	14234	_	_	_	_	_	_	0	_
Edition 10 Package up 525 KR	_	55	14236	_	_	_	_	_	_	_	0
Safety Package	_	4.4	9556	0	0	0	0	0	0	_	_
Safety Package	_	4.4	9556	_	_	_	_	_	_	0	0
Touring Package	_	15	7345	0	0	0	0	0	0	0	0
Miscellaneous											
Registration documents (CoC papers)	_	0	15151	•	•	•	•	•	•	•	•

O Optional equipment ─ Not possible ● Standard equipment ◆ Mandatory △ Not known at the time of publication

ED Edition 10 Package



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the payload. The specified additional weight for packages and optional equipment shows the additional weight compared with the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the mass for optional equipment specified by the manufacturer in the model overviews. This is an imputed

Aero & Aero up

Smile please - the Aero has arrived

The traditional classic in an airy, modern Aero look. The curved rear light moulding with recessed integral tail lights almost looks like a smile. Inside, the clear, bright design immediately puts you in a good mood. Sophisticated and popular layout solutions offer maximum space and flexibility. The Aero Up promises even more flexibility with its comfortable pull-down bed above the seating group.

Technical info	
Overall length, approx.	634 - 773 cm
Overall width, approx.	230 cm
Overall height, approx.	261 cm
Headroom in living area, approx.	198 cm

Maximum values partly not possible for all models or only in connection with certain options.

Upholstery







+ Upholstery Skagen



+ Upholstery Visby

0

Wood décor



+ Wood décor Maryland Oak

O optionally available

Plus factors

- + I know you: the popular, sophisticated floor plan solutions meet everyone's requirements
- + Winter is coming: be prepared for colder temperatures with the optional Winter Comfort Package
- + Protects you from bad weather: roof, front and rear made of robust GRP
- A real eye-catcher: the new, modern exterior design turns heads and the interior design has a winning concept
- + Aero up with standard fold-down bed (200 x 140 cm sleeping area) above the seating group

































Aero & Aero up Technical info









Aero & Aero up		410 QS	470 EL	470 FR	470 FSK
Standard chassis		Lightweight chassis, 1300 kg	Lightweight chassis, 1360 kg	Lightweight chassis, 1360 kg	Lightweight chassis, 1360 kg
Overall length, approx.	cm	634	683	695	696
Body length approx.	cm	513	562	575	566
Overall width, approx.	cm	230	230	230	230
Overall height, approx.	cm	261	261	261	261
Circumferential dimension awning approx.	cm	918	971	980	971
Headroom in living area, approx.	cm	198	198	198	198
Thickness floor / side walls / roof	mm	39 / 28 / 28	39 / 28 / 28	39 / 28 / 28	39 / 28 / 28
Tire size		185 R14 8PR	185 R14 8PR	185 R14 8PR	185 R14 8PR
Bed dimension: Front bed, L x W, approx.	cm	210 x 135	210 x 85 / 190 x 85 / 210 - 190 x 210 O	200 x 145 - 110	200 x 145 - 110
Bed dimension: Central / middle bed, L X W, approx.	cm				190 x 100
Bed dimension: Rear bed, L x W, approx.	cm	190 x 135	210 x 130 - 100	210 x 125	2x 210 x 80 / 2x 210 x 80 O / 210 x 70 O
Sleeping berths standard / max.		3	3	4	5/60
Mass in running order (+/-5%)*	kg	1110 (1055 to 1166)*	1240 (1178 to 1302)*	1210 (1150 to 1271)*	1210 (1150 to 1271)*
$\label{eq:mass_period} \mbox{Manufacturer-specified mass for optional equipment}^*$	kg	109	34	53	43
Technically permissible maximum laden mass*	kg	1300	1360	1360	1360
Heating		S 3004, 3.5 kW Gas / Combi 6 G/E, 6 kW Gas-Electric O	S 3004, 3.5 kW Gas / Combi 6 G/E, 6 kW Gas-Electric O	S 3004, 3.5 kW Gas / Combi 6 G/E, 6 kW Gas-Electric O	Combi 6 G/E, 6 kW Gas-Electric
Refrigerator volume (thereof freezer), approx.	1	78 (11)	137 (15)	137 (15)	137 (15)
Waste water tank, approx.	I	23	23	23	23
Fresh water tank capacity, total/ Fresh water tank capacity driving filling	ty at	44 / 15	44 / 15	44 / 15	44 / 15
Sockets: 12 V / 230 V / USB		0/8/1	0/9/1	0/9/1	0/9/1



The specified mass in running order is a standard value defined in the type approval procedure. Due to manufacturing tolerances, the actual weighed mass in running order may deviate from the value stated above. Deviations of up to \pm 5% of the mass in running order are legally permissible and possible. The permissible range in kilograms is stated in parentheses after the mass in running order. The mass for optional equipment specified by the manufacturer is an imputed value determined for each type and layout by which Dethleffs specifies the maximum weight available for factory-fitted optional equipment. The purpose of limiting optional equipment is to ensure that the minimum payload, i.e. the legally required free mass for baggage and retrofitted accessories, is actually available for the load capacity of vehicles delivered by

Aero & Aero up Technical info









Aero & Aero up		490 QSK	500 QSK	510 ER	520 ER
Standard chassis		Lightweight chassis, 1500 kg	Lightweight chassis, 1500 kg	Lightweight chassis, 1500 kg	Lightweight chassis, 1500 kg
Overall length, approx.	cm	720	726	731	751
Body length approx.	cm	595	605	615	635
Overall width, approx.	cm	230	230	230	230
Overall height, approx.	cm	261	261	261	261
Circumferential dimension awning approx.	cm	1000	1010	1020	1040
Headroom in living area, approx.	cm	198	198	198	198
Thickness floor / side walls / roof	mm	39 / 28 / 28	39 / 28 / 28	39 / 28 / 28	39 / 28 / 28
Tire size		185 R14 8PR	185 R14 8PR	185 R14 8PR	185 R14 8PR
Bed dimension: Front bed, L x W, approx.	cm	210 x 135	210 x 145	200 x 85 / 190 x 85 / 200 x 195 O	200 x 85 / 195 x 85 / 200 x 195 O
Bed dimension: Central / middle bed, L X W, approx.	cm	200 x 90	190 x 90		
Bed dimension: Rear bed, L x W, approx.	cm	2x 180 x 70 / 2x 180 x 70 O / 165 x 65 O	2x 210 x 80 / 2x 210 x 80 O / 210 x 70 O	210 x 145 - 90	210 x 145 - 125
Sleeping berths standard / max.		5/60	5 / 6 🔿	4	4
Mass in running order (+/-5%)*	kg	1270 (1207 to 1334)*	1270 (1207 to 1334)*	1300 (1235 to 1365)*	1330 (1264 to 1397)*
Manufacturer-specified mass for optional equipment*	kg	121	120	99	67
Technically permissible maximum laden mass*	kg	1500	1500	1500	1500
Heating		S 3004, 3.5 kW Gas / Combi 6 G/E, 6 kW Gas-Electric O	S 3004, 3.5 kW Gas / Combi 6 G/E, 6 kW Gas-Electric O	S 3004, 3.5 kW Gas / Combi 6 G/E, 6 kW Gas-Electric O	S 3004, 3.5 kW Gas / Combi 6 G/E, 6 kW Gas-Electric O
Refrigerator volume (thereof freezer), approx.	1	137 (15)	137 (15)	137 (15)	137 (15)
Waste water tank, approx.	I	23	23	23	23
Fresh water tank capacity, total/ Fresh water tank capacit driving filling	y at	44 / 15	44 / 15	44 / 15	44 / 15
Sockets: 12 V / 230 V / USB		0/9/1	0/9/1	0/9/1	0/9/1



The specified mass in running order is a standard value defined in the type approval procedure. Due to manufacturing tolerances, the actual weighed mass in running order may deviate from the value stated above. Deviations of up to \pm 5% of the mass in running order are legally permissible and possible. The permissible range in kilograms is stated in parentheses after the mass in running order. The mass for optional equipment specified by the manufacturer is an imputed value determined for each type and layout by which Dethleffs specifies the maximum weight available for factory-fitted optional equipment. The purpose of limiting optional equipment is to ensure that the minimum payload, i.e. the legally required free mass for baggage and retrofitted accessories, is actually available for the load capacity of vehicles delivered by

Aero & Aero up Technical info







Aero & Aero up		up 460 KR	up 530 ER	up 530 KR
Standard chassis		Lightweight chassis, 1600 kg	Lightweight chassis, 1600 kg	Lightweight chassis, 1600 kg
Overall length, approx.	cm	680	773	771
Body length approx.	cm	556	648	648
Overall width, approx.	cm	230	230	230
Overall height, approx.	cm	261	261	261
Circumferential dimension awning approx.	cm	972	1065	1065
Headroom in living area, approx.	cm	198	198	198
Thickness floor / side walls / roof	mm	39 / 28 / 28	39 / 28 / 28	39 / 28 / 28
Tire size		185 R14 8PR	185 R14 8PR	185 R14 8PR
Bed dimension: Front bed, L x W, approx.	cm	210 x 73 / 213 x 91	2x 205 x 88 / 205 x 208 O	200 x 74 / 205 x 77 / 177 x 69
Bed dimension: Central / middle bed, L X W, approx.	cm			
Bed dimension: Rear bed, L x W, approx.	cm	200 x 144 / 213 x 155	200 x 144 / 213 x 155	200 x 144 / 213 x 155
Sleeping berths standard / max.		4	4	4
Mass in running order (+/-5%)*	kg	1290 (1226 to 1355)*	1405 (1335 to 1475)*	1405 (1335 to 1475)*
Manufacturer-specified mass for optional equipment*	kg	114	90	90
Technically permissible maximum laden mass*	kg	1500	1600	1600
Heating		S 3004, 3.5 kW Gas / Combi 6 G/E, 6 kW Gas-Electric O	S 3004, 3.5 kW Gas / Combi 6 G/E, 6 kW Gas-Electric O	S 3004, 3.5 kW Gas / Combi 6 G/E, 6 kW Gas-Electric O
Refrigerator volume (thereof freezer), approx.	1	137 (15)	137 (15)	137 (15)
Waste water tank, approx.	I	23	23	23
Fresh water tank capacity, total/ Fresh water tank capacity at driving filling	1	44 / 15	41 / 15	44 / 15
Sockets: 12 V / 230 V / USB		0/5/1	0/9/1	0/9/1

O Optional equipment — Not possible • Standard equipment • Mandatory 🛆 Not known at the time of publication



The specified mass in running order is a standard value defined in the type approval procedure. Due to manufacturing tolerances, the actual weighed mass in running order may deviate from the value stated above. Deviations of up to \pm 5% of the mass in running order are legally permissible and possible. The permissible range in kilograms is stated in parentheses after the mass in running order. The mass for optional equipment specified by the manufacturer is an imputed value determined for each type and layout by which Dethleffs specifies the maximum weight available for factory-fitted optional equipment. The purpose of limiting optional equipment is to ensure that the minimum payload, i.e. the legally required free mass for baggage and retrofitted accessories, is actually available for the load capacity of vehicles delivered by

Standard equipment	410 QS	470 EL	470 FR	470 FSK	490 QSK	500 QSK	510 ER	520 ER	up 460 KR	up 530 ER	up 530 KR
Chassis											
Tyres on steel wheels 185 R14 C 8 PR, up to and including 1.600 kg											
Zinc-plated chassis with inertia braking system with reversing automatic											
Chassis features		Ť		Ť							
	-	-	-	-	•	•	-	-			
AAA self-adjusting brake ACS stabiliser											
High-quality brand-name tyres, designed for a speed of 100 km/h											
Lightweight zinc-plated corner steadies											
Octagon shock absorber		•		•		•	•				
Exterior features											
Floor of the gas bottle locker made of rot-resistant and robust corrugated aluminium											
Front, rear and roof made of robust GRP											
Opening window in bathroom				•			•				
Opening windows, insulated and double-glazed (graphite grey) with blackout and mosquito blinds	•	•	•	•	•	•	•	•	•	•	•
Rear window					_						
Skylight incl. illumination, 400 x 400 mm	•	•	•	•	•	•	•	•	•	•	•
Skylight, 400 x 400 mm									•	•	
Space-saving gas locker door which opens upwards	•	•	•	•	•	•	•	•	•	•	
Spare wheel carrier in gas locker									•		
Storage space for 2 gas bottles with 11 kg filling weight each	•	•	•	•	•	•	•	•	•	•	•
Wide, one-piece habitation door with window	•	•	•	•	•	•	•	•	•	•	•
Exterior design											
Design element for front									•		
Design element for rear	•	•	•	•	•	•	•	•	•	•	•
Sides in hammer finish, white	•	•	•	•	•	•	•	•	•	•	•
Access locker doors											
Access locker door front right side 1000x420 mm				_					_	•	_
Access locker door front right side 1675x885 mm	_	_	_	_	_	_	_	_	_	_	•
Access locker door front right side 560x1150 mm	_	_	_	_	_	_	_	_		-	_
Access locker door rear left side 1000x420 mm ⁷⁾	_	_	_	_	•	_	_	_	_	_	_
Interior design											
Upholstery Fyn	•	•	•	•	•	•	•	•	•	•	•
Wood décor Maryland Oak	•	•	•	•	•	•	•	•	•	•	
Textile equipment											
7-zones mattress, made of heat-regulating material	•	•	•	•	•	•	•	•	•	•	•
Furniture layouts											
AirPlus - perfect air circulation in the interior and rear ventilation of the overhead lockers and sideboards	•	•	•	•	•	•	•	•	•	•	
Bunk bed with 2 sleeping berths, foldable	_	_	_	•	•	•	_	_	•	_	•
Bunk beds with safety net and ladder	_	_	_				_	_		-	
One-legged telescopic table, height adjustable	_	_	•	_	_	_	•	•	•	•	•
Seating lounge converts to bed											
Spacious pull-down bed above seating lounge, with manual control	_					_		_			
Special slatted frame with flexible natural rubber holders, opening for optimal use of storage compartments under the beds	•	•	•	•	•	•	•	•	_	-	_
Interior features											
Smoke detector	•	•	•	•	•	•	•	•	•	•	•
Kitchen											
Generous drawers with soft closing for absolutely silent closing	•	•	•	•	•	•	•	•	•	•	•
Large fridge with 137 liters capacity and 15 liters freezer compartment	_	•	•	•	•	•	•	•	•	•	•
Practical 3-flames cooker with electric ignition								•	•	•	•
Spacious fridge with 78 liters volume and 11 liters freezer compartment	•	_	-	_	-	_	_	_	_	_	-

Standard equipment	410 QS	470 EL	470 FR	470 FSK	490 QSK	500 QSK	510 ER	520 ER	up 460 KR	up 530 ER	up 530 KR
Bathroom											
Integrated design washbasin made of solid surface material	•	•	•	•	•	•	•	•	•	•	
Shower tray		•									
Skylight with mosquito net	•	•	•	•	•	•	•	•	•	•	
Heating											
Gas heating S 3004 with automatic ignition	•	•	•	-	•	•	•	•	•	•	•
Electrical installation											
12 V power supply throughout vehicle	•	•	•	•	•	•	•	•	•	•	•
Additional lighting through LED spotlights						•	•	•			
Awning light 12V											
CEE external output socket for 230V on-board electrics											
Compact power distribution unit with 230V safety device and 12V fuse box in wardrobe incl. powerful 340W transformer	•	•	•	•	•	•	•	•	•	•	•
LED spots in front and rear seating lounges											
USB port for spotlight bar	•	•		•	•	•	•	•	•	•	
Water supply											
Electric water supply	•	•	•	•	•	•	•	•	•	•	•
Fresh water tank 44 l											
Mobile 22 I waste water tank	•		•	•	•	•	•	•	•	•	
Miscellaneous											
Dethleffs Connect - System Information Unit: SIU control unit incl. voltage and levelling display via the											_

Dethleffs app.

Packages Aero & Aero up

Package	Styling Package white (13252)	Styling Package white (13252)
Smooth sides white	Х	
17" alloy wheels in Dethleffs design (single axle)	X	Х
Draw bar cover	X	X
Corner steadies incl. large-area support feet	X	X
Solid rubber support wheel with support load indicator	X	X
Smooth sides white		X
Additional weight (kg)*	26	26

Package	Safety Package (9556)
ATC Trailer Control	х
DuoControl safety gas pressure regulator with crash sensor and EisEx gas regulator heater	
Additional weight (kg)*	4.4

Package	Autonomy Package I (10011)	Autonomy Package II (10012)
Battery (95 Ah)	Х	Х
Battery charger	X	X
Central 12V main switch	X	X
Voltage display	Х	X
Fan 12V for S 3004	X	
Additional weight (kg)*	31	29

Package	Winter Comfort Package (11547)	Winter Comfort Package (11547)	Winter Comfort Package for Combi heating (13028)
Hot air heating Combi 6 G/E incl. digital control unit	Х	Х	
Digital control panel for Combi heating (G/E only)	Х	Х	
Electric floor heating	х	Х	x
XPS insulation for front, rear and sides (depending on vehicle size)	х		x
XPS insulation for front, rear and sides (depending on vehicle size)		Х	
Additional weight (kg)*	21	21	6



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the payload. The specified additional weight for packages and optional equipment shows the additional weight compared with the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the mass for optional equipment specified by the manufacturer in the model overviews. This is an imputed

Package	Touring Package (13251)	Touring Package (13411)
Hot water supply	X	
Flyscreen door	X	Х
Hot air system	X	Х
Skylight incl. illumination, 700 x 500 mm	X	Х
Additional weight (kg)*	15	13

Shower Package (6105)

City water connection

Shower equipment with shower fittings and curtain

Additional weight (kg)*

 \triangle Not known at the time of publication



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the payload. The specified additional weight for packages and optional equipment shows the additional weight compared with the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the mass for optional equipment specified by the manufacturer in the model overviews. This is an imputed

Optional equipment*	Included in package	Additional weight (kg)*	Code	410 QS	470 EL	470 FR	470 FSK	490 QSK	500 QSK	510 ER	520 ER	up 460 KR	up 530 ER	up 530 KR
Chassis														
17" alloy wheels in Dethleffs design (single axle)	_	1	11608	0	0	0	0	0	0	0	0	0	0	0
Tyres on alloy wheels 185 R14 C LI102, up to and including 1600 kg	_	1	836	0	0	0	0	0	0	0	0	0	0	0
Tyres on alloy wheels 195 R14 C LI106, 1700 kg and 1800 kg	_	1	838	0	0	0	0	0	0	0	0	0	0	0
Weight upgrade														
Weight upgrade 1.700 kg (incl. steel wheel 195 R14 C LI106)	_	36	278	0	_	0	0		_	_	_	_	_	_
Weight upgrade 1.700 kg (incl. steel wheel 195 R14 C LI106)	_	8	278	_	_	_	_	0	0	0	0	_	_	_
Weight upgrade 1.700 kg (incl. steel wheel 195 R14 C LI106)	_	7	278	_	_	_	_	_	_	_	_	0	0	_
Weight upgrade 1.700 kg (incl. steel wheel 195 R14 C LI106)	_	6	278	_	_	_	_	_	_	_	_	_	_	0
Weight upgrade 1.700 kg (incl. steel wheel 195 R14 C LI106)	_	35	278	_	0	_	_	_	_	_	_	_	_	_
Weight upgrade 1.800 kg (incl. steel wheel 195 R14 C LI106)	_	8	279	_	_	_	_	0	0	0	0	_	_	_
Weight upgrade 1.800 kg (incl. steel wheel 195 R14 C LI106)	_	6	279	_	_	_	_	_	_	_	_	_	_	0
Weight upgrade 1.800 kg (incl. steel wheel 195 R14 C LI106)	_	7	279	_	_	_	_	_	_	_	_	0	0	_
Weight upgrade 1.900 kg (incl. alloy wheel 225/70 R15 C LI112)	_	27	394	_	_	_	_	_	_	_	_	_	0	0
Weight upgrade 2.000 kg (incl. alloy wheel 225/70 R15 C LI112)	_	27	138	_	_	_	_	_	_	_	_	_	0	0
Weight upgrade to 1.360 kg (without chassis change)	_	0	9619	0	_	_	_	_	_	_	_	_	_	_
Weight upgrade to 1.400 kg	_	0	359	0	0	0	0	_	_	_	_	_	_	_
Weight upgrade to 1.500 kg	_	0	136	0	0	0	0	_	_	_	_	_	_	_
Weight upgrade to 1.600 kg	_	0	322	_	_	_	_	_	_	_	_	0	_	_
Chassis features														
ATC Trailer Control	_	4	748	0	0	0	0	0	0	0	0	0	0	0
Corner steadies incl. large-area support feet	_	4	9138	0	0	0	0	0	0	0	0	0	0	0
Draw bar cover	_	2	434	0	0	0	0	0	0	0	0	0	0	0
Solid rubber support wheel with support load indicator	_	2	10063	0	0	0	0	0	0	0	0	0	0	0
Spare tyre with alloy wheel 185 R14 C LI 102, up to and including 1.600 kg	-	17	837	0	0	0	0	0	0	_	0	0	0	0
Spare tyre with alloy wheel 195 R14 C 8PR-LI 106, 1.700 kg and 1.800 kg	_	19	839	_	0	0	0	0	0	_	0	0	0	0
Spare tyre with alloy wheel 215/60 R17 C LI 109	_	24.1	11540	0	0	0	0	0	0	_	0	_	_	_
Spare tyre with alloy wheel 225/70 R15 C LI 112 , 1.900 kg and 2.000 kg	_	23.5	1092	_	_	_	_	_	_	_	_	_	0	0
Spare tyre with steel wheel 185 R14 C 8 PR, up to and including 1.600 kg	-	18	831	0	0	0	0	0	0	-	0	0	0	0
Spare tyre with steel wheel 195 R14 C LI 106, 1.700 kg and 1.800 kg	_	20.4	833	_	0	0	0	0	0	_	0	0	0	0
Wheel trims for 14" tyres	_	0.5	276	0	0	0	0	0	0	0	0	0	0	0
Exterior features														
Flyscreen door	_	3	360	0	0	0	0	0	0	0	0	0	0	0
Front window	_	3	982	0	0	0	0	0	0	0	0	_	0	0
Kitchen window, sliding (change of window shape)	_	3	6406	0	0	0	0	0	0	0	0	0	0	0
Skylight incl. illumination, 700 x 500 mm	_	10	11575	0	0	0	0	0	0	0	0	0	0	0
Exterior design														
Smooth sides white	_	17	443	0	0	0	0					0		
Smooth sides white	_	17	443	_	_	_	_	0	0	0	0	_	0	0
Access locker doors														
		2	(445		-		6	_	_	_	_		_	
Access locker door front left side 1000x420 mm	_	2	6415	0	0	_		0	0	0	0	_	0	



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the payload. The specified additional weight for packages and optional equipment shows the additional weight compared with the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the mass for optional equipment specified by the manufacturer in the model overviews. This is an imputed

Optional equipment*	Included in package	Additional weight (kg)*	Code	410 QS	470 EL	470 FR	470 FSK	490 QSK	500 QSK	510 ER	520 ER	up 460 KR	up 530 ER	up 530 KR
Access locker door rear left 1675x885 mm ⁷⁾	_	0	10848	_	_	_	_	0	_	_	_	_	_	_
Access locker door rear right side 560x1150 mm	_	2.5	991	_	_	_	_	_	0	_	_	_	_	_
Access locker door rear right side 750x300 mm	_	2	6422	_	_	0	_	_	_	_	_	•	•	•
Interior design														
Upholstery Skagen	_	0	11522	0	0	0	0	0	0	0	0	0	0	0
Upholstery Visby	_	0	11523	0	0	0	0	0	0	0	0	0	0	0
Textile equipment														
Loose carpet	_	7	513	0	0	0	0	0	0	0	0	0	0	0
Furniture layouts														
Bunk bed with 3 sleeping berths, not foldable	-	21	200	-	-	_	0	0	0	-	-	-	-	
Hanging table with rotating device	_	0	8699	0	_	_	_	0	0	_	_	_	_	_
Seat enlargement for opposite seating lounge (in comb. with option 8699) $^{3)}$	_	0	7750	0	-	_	-	0	0	_	_	-	_	_
Single beds convert to double bed	_	6	685	_	0	_	_	_	_	0	0	_	0	_
Multimedia														
Multifunctional external connection, 12 V, 220 V, TV and SAT ⁴⁾	_	1	611	0	0	0	0	0	0	0	0	0	0	0
Preparation for flat screen TV (antenna cable and TV bracket)	_	2	678	0	0	0	0	0	0	0	0	0	0	0
Heating														
Electric floor heating	-	6	387	0	0	0	0	0	0	0	0	0	0	0
Fan 12V for S 3004	_	2	177	0	0	0	_	0	0	0	0	0	0	0
Hot air heating Combi 6 G/E incl. digital control unit	_	15	9427	0	0	0		0	0	0	0	0	0	0
Hot air system		0	142	0	0	0	0	0	0	0	0	0	0	0
Ultraheat additional heating for S 3004, electric 220 V	_	2	364	0	0	0	_	0	0	0	0	0	0	0
Air Conditioning														
Pre-wiring for A/C	_	3.5	172	0	0	0	0	0	0	0	0	0	0	0
Roof A/C		37	6512	0	0	0	0	0	0	0	0	0	0	0
Electrical installation														
Indirect lighting		1	633	0	0	0	0	0	0	0	0	0	0	0
Water supply														
City water connection	_	2	414	0	0	0	0	0	0	0	0	0	0	0
Hot water supply	_	2	123	0	0	0	_	0	0	0	0	0	0	0
Shower equipment with shower fittings and curtain		3	1097	0	0	0	0	0	0	0	0	0	0	0
Gas supply														
DuoControl safety gas pressure regulator with crash sensor and EisEx gas regulator heater	_	0.4	784	0	0	0	0	0	0	0	0	0	0	0
Gas detection system	_	0.5	10058	0	0	0	0	0	0	0	0	0	0	0
Gas socket (exterior) ⁵⁾	_	1	187	0	0	0	0	0	0	0	0	0	0	0
Packages														
Autonomy Package I		31	10011	0	0	0	=	0	0	0	0	0	0	0
Autonomy Package II	-	29	10012	0	0	0	0	0	0	0	0	0	0	0
Safety Package	_	4.4	9556	0	0	0	0	0	0	0	0	0	0	0
Shower Package	-	5	6105	0	0	0	0	0	0	0	0	0	0	0
Styling Package white	_	26	13252	0	0	0	0	_	_	_	-	0	-	_



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the payload. The specified additional weight for packages and optional equipment shows the additional weight compared with the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the mass for optional equipment specified by the manufacturer in the model overviews. This is an imputed

Optional equipment*	Included in package	Additional weight (kg)*	Code	410 QS	470 EL	470 FR	470 FSK	490 QSK	500 QSK	510 ER	520 ER	up 460 KR	up 530 ER	up 530 KR
Styling Package white	_	26	13252	_	_	_	_	0	0	0	0	_	0	0
Touring Package	_	13	13411	_	_	_	0	_	_	_	_	_	_	_
Touring Package	_	15	13251	0	0	0	_	0	0	0	0	0	0	0
Winter Comfort Package	_	21	11547	0	0	0	_	_	_	_	_	0	_	_
Winter Comfort Package	_	21	11547	_	_	_	_	0	0	0	0	_	0	0
Winter Comfort Package for Combi heating	_	6	13028	_	_	_	0	_	_	_	_	_	_	_
Miscellaneous														
Registration documents (CoC papers)	_	0	15151	*	*	*	*	*						

O Optional equipment - Not possible lacktriangle Standard equipment lacktriangle Mandatory Δ Not known at the time of publication



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the payload. The specified additional weight for packages and optional equipment shows the additional weight compared with the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the mass for optional equipment specified by the manufacturer in the model overviews. This is an imputed

Camper®

The family caravan

With its extensive standard equipment, abundant storage space and a wide range of bunk bed layouts and compact designs, the Camper® is the ideal caravan for all those of you who love adventure.

Technical info Overall length, approx. 691 - 942 cm Overall width, approx. 230 - 250 cm Overall height, approx. 265 cm Headroom in living area, approx. 198 cm

Maximum values partly not possible for all models or only in connection with certain options.

Upholstery







+ Upholstery Galaxy
O



+ Upholstery Mount

0

Wood décor



+ Wood décor Rosario Cherry

O optionally available

Plus factors

- + Enough space for every child: a selection of family layouts with bunk beds
- + Better safe than sorry: exemplary Dethleffs safety equipment
- + Good as standard: ready to go thanks to comprehensive specifications
- + Modern interior: three classic upholstery options
- + Kitted out for all needs: our portfolio even features short caravans less than 7 m in length



























Camper® Technical info









Camper®		460 EL	500 QSK	510 LE	530 FSK
Standard chassis		Lightweight chassis, 1500 kg	Lightweight chassis, 1500 kg	Lightweight chassis, 1600 kg	Lightweight chassis, 1600 kg
Overall length, approx.	cm	691	729	762	788
Body length approx.	cm	550	590	630	650
Overall width, approx.	cm	230	230	230	230
Overall height, approx.	cm	265	265	265	265
Circumferential dimension awning approx.	cm	948	988	1028	1048
Headroom in living area, approx.	cm	198	198	198	198
Thickness floor / side walls / roof	mm	42 / 34 / 34	42 / 34 / 34	42 / 34 / 34	42 / 34 / 34
Tire size		185 R14C 8PR	185 R14C 8PR	185 R14C 8PR	185 R14C 8PR
Bed dimension: Front bed, L x W, approx.	cm	200 x 85 / 190 x 85 / 190 x 210 O	210 x 135	210 x 135	200 x 135
Bed dimension: Central / middle bed, L X W, approx.	cm		190 x 100		190 x 100
Bed dimension: Rear bed, L x W, approx.	cm	210 x 115	210 x 70 / 195 x 75 / 210 x 75 O / 210 x 80 O / 210 x 70 O	2x 200 x 85 / 195 x 210 O	210 x 70 / 195 x 75 / 210 x 75 O / 210 x 80 O / 210 x 70 O
Sleeping berths standard / max.		3	5 / 6 🔿	4	5/60
Mass in running order (+/-5%)*	kg	1235 (1173 to 1297)*	1295 (1230 to 1360)*	1315 (1249 to 1381)*	1385 (1316 to 1454)*
$\label{eq:mass} \mbox{Manufacturer-specified mass for optional equipment}^*$	kg	180	96	182	100
Technically permissible maximum laden mass*	kg	1500	1500	1600	1600
Heating		S 3004, 3.5 kW Gas / Combi 4 G/E, 4 kW Gas-Electric O	S 3004, 3.5 kW Gas / Combi 4 G/E, 4 kW Gas-Electric O	S 3004, 3.5 kW Gas / Combi 4 G/E, 4 kW Gas-Electric O	S 5004, 6 kW Gas / Combi 6 G/E, 6 kW Gas-Electric O / Hot water heating, 6.4 kW Gas-Electric O
Refrigerator volume (thereof freezer), approx.	1	137 (15)	137 (15)	137 (15)	137 (15)
Waste water tank, approx.	I	22	22	22	22
Fresh water tank capacity, total/ Fresh water tank capacit driving filling	y at	43 / 15	43 / 15	43 / 15	43 / 15
Sockets: 12 V / 230 V / USB		0/7/1	0/8/3	0/7/1	0 / 7 / 3



The specified mass in running order is a standard value defined in the type approval procedure. Due to manufacturing tolerances, the actual weighed mass in running order may deviate from the value stated above. Deviations of up to \pm 5% of the mass in running order are legally permissible and possible. The permissible range in kilograms is stated in parentheses after the mass in running order. The mass for optional equipment specified by the manufacturer is an imputed value determined for each type and layout by which Dethleffs specifies the maximum weight available for factory-fitted optional equipment. The purpose of limiting optional equipment is to ensure that the minimum payload, i.e. the legally required free mass for baggage and retrofitted accessories, is actually available for the load capacity of vehicles delivered by

Camper® Technical info









Camper®		540 QМК	550 ESK	560 FMK	730 FKR
Standard chassis		Lightweight chassis, 1700 kg	Lightweight chassis, 1600 kg	Lightweight chassis, 1700 kg	Lightweight chassis, 2000 kg
Overall length, approx.	cm	768	806	818	942
Body length approx.	cm	650	675	675	805
Overall width, approx.	cm	250	230	250	250
Overall height, approx.	cm	265	265	265	265
Circumferential dimension awning approx.	cm	1048	1078	1078	1208
Headroom in living area, approx.	cm	198	198	198	198
Thickness floor / side walls / roof	mm	42 / 34 / 34	42 / 34 / 34	42 / 34 / 34	42 / 34 / 34
Tire size		195 R14C LI106	185 R14C 8PR	195 R14C LI106	185/70 R14 LI88
Bed dimension: Front bed, L x W, approx.	cm	200 x 140	2x 200 x 85 / 200 x 210 O	200 x 155	200 x 155
Bed dimension: Central / middle bed, L X W, approx.	cm	230 x 115	190 x 100	230 x 115	200 x 75 / 2x 195 x 75 / 2x 195 x 75 O
Bed dimension: Rear bed, L x W, approx.	cm	190 x 75 / 190 x 70 / 2x 190 x 75 O / 170 x 75 O	210 x 70 / 200 x 75 / 210 x 75 O / 210 x 80 O / 210 x 70 O	195 x 70 / 190 x 75 / 195 x 75 ○ / 195 x 80 ○ / 195 x 70 ○	230 x 155
Sleeping berths standard / max.		5/60	5/60	5/60	7/80
Mass in running order (+/-5%)*	kg	1475 (1401 to 1549)*	1435 (1363 to 1507)*	1525 (1449 to 1601)*	1815 (1724 to 1906)*
Manufacturer-specified mass for optional equipment*	kg	110	48	58	35
Technically permissible maximum laden mass*	kg	1700	1600	1700	2000
Heating		S 5004, 6 kW Gas / Combi 6 G/E, 6 kW Gas-Electric O / Hot water heating, 6.4 kW Gas-Electric O	S 5004, 6 kW Gas / Combi 6 G/E, 6 kW Gas-Electric O / Hot water heating, 6.4 kW Gas-Electric O	S 5004, 6 kW Gas / Combi 6 G/E, 6 kW Gas-Electric O / Hot water heating, 6.4 kW Gas-Electric O	S 5004, 6 kW Gas / Combi 6 G/E, 6 kW Gas-Electric O / Hot water heating, 6.4 kW Gas-Electric O
Refrigerator volume (thereof freezer), approx.	1	137 (15)	137 (15)	137 (15)	86 (11) / 156 (29) O
Waste water tank, approx.	I	22	22	22	22
Fresh water tank capacity, total/ Fresh water tank capacity driving filling	y at	43 / 15	43 / 15	43 / 15	43 / 15



* INFO

The specified mass in running order is a standard value defined in the type approval procedure. Due to manufacturing tolerances, the actual weighed mass in running order may deviate from the value stated above. Deviations of up to \pm 5% of the mass in running order are legally permissible and possible. The permissible range in kilograms is stated in parentheses after the mass in running order. The mass for optional equipment specified by the manufacturer is an imputed value determined for each type and layout by which Dethleffs specifies the maximum weight available for factory-fitted optional equipment. The purpose of limiting optional equipment is to ensure that the minimum payload, i.e. the legally required free mass for baggage and retrofitted accessories, is actually available for the load capacity of vehicles delivered by

Camper® Technical info









Camper®	540 QMK	550 ESK	560 FMK	730 FKR
Sockets: 12 V / 230 V / USB	0/8/3	0/8/3	0/9/3	0 / 10 / 3

O Optional equipment — Not possible • Standard equipment • Mandatory \triangle Not known at the time of publication



The specified mass in running order is a standard value defined in the type approval procedure. Due to manufacturing tolerances, the actual weighed mass in running order may deviate from the value stated above. Deviations of up to $\pm\,5\%$ of the mass in running order are legally permissible and possible. The permissible range in kilograms is stated in parentheses after the mass in running order. The mass for optional equipment specified by the manufacturer is an imputed value determined for each type and layout by which Dethleffs specifies the maximum weight available for factory-fitted optional equipment. The purpose of limiting optional equipment is to ensure that the minimum payload, i.e. the legally required free mass for baggage and retrofitted accessories, is actually available for the load capacity of vehicles delivered by

Standard equipment	460 EL	500 QSK	510 LE	530 FSK	540 QMK	550 ESK	560 FMK	730 FKR
Chassis								
Single axle premium wheel 195 R14 C LI106 (with steel wheel 1.700 kg and 1.800 kg)	_	_	_	_	•	_	•	_
Tyres on steel wheels 185 R14 C 8 PR, up to and including 1.600 kg					_		_	_
Tyres on steel wheels 185/70 R14 L188 up to and including 2.000 kg	_	_	_	_	_	_	_	
Zinc-plated chassis with inertia braking system with reversing automatic	•	•	•	•	•	•	•	
Chassis features								
AAA self-adjusting brake								
ACS stabiliser	•	•	•	•	•	•	•	•
High-quality brand-name tyres, designed for a speed of 100 km/h								
Lightweight corner steadies	•	•	•	•	•	•	•	•
Octagon shock absorber	•	•	•	•	•	•	•	•
Exterior features								
Floor of the gas bottle locker made of rot-resistant and robust corrugated aluminium	•						•	
Flyscreen door	•	•	•	•	•	•	•	•
Front parts in gas locker area made of LFI (long fiber injection) technology, shock resistant, robust and repair-friendly								
Fully-insulated wheel houses	•	•	•	•	•	•	•	•
Midi Heki lift-and-tilt skylight incl. illuminated roof lining								
One-piece habitation door	•	•	•				•	
Opening window in bathroom	_	_	_			_		
Opening windows, trapezoid, insulated and double-glazed (graphite grey) with blackout and mosquito blinds	•	•	•	•	•	•	•	
Robust GRP roof								
Sidewall skirts with integrated side-marker lamps		•	•					
Skylight Mini Heki Space-saving gas locker door which opens upwards								
Spare wheel carrier in gas locker Storage space for 2 gas bottles with 11 kg filling weight each								
		Ť						Ť
Exterior design								
Front and rear in smooth sides white		•	•	•	•	•	•	
Sides in hammer finish, white	•	•	•	•	•	•	•	
Access locker doors								
Access locker door front right side 997x419 mm			_		_		_	_
Access locker door rear right side997x419 mm	_	_	•	_	_	_	_	_
Interior design								
Upholstery Cloud	•	•	•	•	•	•	•	
Wood décor Rosario Cherry	•	•		•	•	•	•	•
Textile equipment								
7-zones double bed mattress, made of heat-regulating material	_	•	_	•	•	_	•	•
7-zones mattress left side, made of heat-regulating material	•	_	•	_	_	•	_	_
7-zones mattress right side, made of heat-regulating material		_		_	_		_	_
Furniture layouts								
AirPlus - perfect air circulation in the interior and rear ventilation of the overhead lockers and sideboards	•	•	•	•	•	•	•	•
Bunk bed with 2 sleeping berths, foldable	_	•	_	•	•	•	•	_
Bunk bed with 2 sleeping berths, not foldable	_	_	_	_	_	_	_	
Bunk beds with safety net and ladder	_	•	_	•	•	•	•	•
One-legged telescopic table, height adjustable	_	_	_	_		_		•
Seating lounge converts to bed	•	•	•	•	•	•	•	•
Special slatted frame with flexible natural rubber holders, opening for optimal use of storage compartments under the								
beds								
Kitchen								
Generous drawers with soft closing for absolutely silent closing								
Large fridge with 137 liters capacity and 15 liters freezer compartment								_

Standard equipment	460 EL	500 QSK	510 LE	530 FSK	540 QMK	550 ESK	560 FMK	730 FKR
Practical 3-flames cooker with electric ignition			•	•				
Practical apothecary drawers (depending on layout)	•		•	•	•	•	•	•
Spacious fridge with 86-litre volume and 11 litre freezer	_	_	_	_	_	_	_	
Bathroom								
Integrated design washbasin made of solid surface material		•	•	•	•	•	•	
Shower tray	•	•	•	•	•	•		•
Skylight with mosquito net	•	•	•	•				•
Heating								
Gas heating S 3004 with automatic ignition	•	•	•	-	-	-	-	_
Gas heating S 5004 with automatic ignition	_	_	_	•	•	•	•	•
Hot air system	•	•	•	•	•	•		•
Electrical installation								
12 V power supply throughout vehicle	•	•	•	•	•	•	•	•
Awning light 12V								
CEE external output socket for 230V on-board electrics								
Compact power distribution unit with 230V safety device and 12V fuse box in wardrobe incl. powerful 340W transformer	•	•	•	•	•	•	•	•
LED light bar system 12V (on head-side of bed and in seating lounge)								
USB port for spotlight bar	•	•	•	•	•	•	•	•
Water supply								
Electric water supply	•	•	•	•	•	•	•	•
Fresh water tank 38 l								
Hot water supply	•	•	•	•	•	•	•	•
Mobile 22 I waste water tank								

Packages Camper®

Package	Styling Package white (single axle) (13254)	Styling Package white (single axle) (13254)	Styling Package white (single axle) (13254)	Styling Package white (tandem axle) (13256)	Styling Package white (tandem axle 2.8 t) (13258)
Smooth sides white	Х				
17" alloy wheels in Dethleffs design (single axle)	Х	Х	Х		
Draw bar cover	Х	х	Х	Х	x
Large support feet, 4 pc.	Х	Х	Х	Х	x
Solid rubber support wheel with support load indicator	Х	Х	Х	Х	x
Manoeuvring handles in chrome design	Х	х	Х	Х	x
Rear light carrier with high attachment and roof rails	Х	Х	Х	Х	x
Front moulding with high attachment and roof rails	Х	Х	Х	Х	х
Smooth sides white		Х			
Smooth sides white			Х		
17" alloy wheels in Dethleffs design (tandem axle)				Х	
Smooth sides white				Х	x
Tyres on alloy wheels 195/70 R14 C LI104, 2200 kg to 2800 kg					х
Additional weight (kg)*	45.7	48.3	51.1	43.4	47.4

Package	Styling Package silver (single axle) (13255)	Styling Package silver (single axle) (13255)	Styling Package silver (single axle) (13255)	Styling Package silver (tandem axle) (13257)	Styling Package silver (tandem axle 2.8 t) (13259)
Smooth sides titanium silver metallic	Х				
17" alloy wheels in Dethleffs design (single axle)	Х	х	х		
Draw bar cover	Х	х	х	х	х
Large support feet, 4 pc.	Х	х	х	х	Х
Solid rubber support wheel with support load indicator	Х	Х	X	X	Х
Manoeuvring handles in chrome design	Х	Х	X	X	X
Rear light carrier with high attachment and roof rails	Х	х	х	х	х
Front moulding with high attachment and roof rails	Х	Х	X	х	Х
Smooth sides titanium silver metallic		Х			
Smooth sides titanium silver metallic			X		
17" alloy wheels in Dethleffs design (tandem axle)				х	
Smooth sides titanium silver metallic				Х	х
Tyres on alloy wheels 195/70 R14 C L1104, 2200 kg to 2800 kg					Х
Additional weight (kg)*	45.7	48.3	51.1	43.4	47.4



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the payload. The specified additional weight for packages and optional equipment shows the additional weight compared with the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the mass for optional equipment specified by the manufacturer in the model overviews. This is an imputed

Package	Winter Comfort Package Combi 4 (10479)	Winter Comfort Package Combi 4 (10479)	Winter Comfort Package Combi 6 (9536)	Winter Comfort Package Combi 6 (9536)	Winter Comfort Package Combi 6 (9536)
Digital control panel for Combi heating (G/E only)	Х	Х	Х	Х	х
Electric floor heating	Х	Х	Х	Х	х
Waste water pipes insulated and heated	Х	Х	Х	Х	х
Insulated threader hose	Х	Х	Х	Х	х
XPS insulation for front, rear and sides (depending on vehicle size)	Х				
Hot air heating Combi 4 G/E incl. digital control unit	Х	Х			
XPS insulation for front, rear and sides (depending on vehicle size)		Х	Х		
Hot air heating Combi 6 G/E incl. digital control unit			X	X	х
XPS insulation for front, rear and sides (depending on vehicle size)				Х	
XPS insulation for front, rear and sides (depending on vehicle size)					x
Additional weight (kg)*	47.6	50.1	50.1	52.8	55

Package	Winter Comfort Package SNOW (5459)	Winter Comfort Package SNOW (5459)	Winter Comfort Package SNOW (5459)	Winter Comfort Package SNOW PLUS (5551)	Winter Comfort Package SNOW PLUS (5551)	Winter Comfort Package SNOW PLUS (5551)
Hot water heating	Х	Х	Х	Х	Х	х
Electric floor heating	Х	х	х			
Waste water pipes insulated and heated	Х	х	Х	х	Х	х
XPS insulation for front, rear and sides (depending on vehicle size)	Х			х		
XPS insulation for front, rear and sides (depending on vehicle size)		х			Х	
XPS insulation for front, rear and sides (depending on vehicle size)			х			х
Hot water floor heating (only in comb. with option 205)				Х	Х	х
Additional weight (kg)*	74.1	76.8	79	75.1	77.8	80

Package	Mover Autonomy Package (single axle) (5560)	Mover Autonomy Package (tandem axle) (5561)
Mover manoeuvring support for single-axle	Х	
Electric Autonomy equipment	X	X
Mover manoeuvring support for tandem-axle		X
Additional weight (kg)*	70	98



Package	Water and Electric Autonomy Package Combi 4 (11031)	Water and Electric Autonomy Package Combi 6 (11032)	Water & Electric Autonomy Package with Combi or hot water heating system (9943)
Hot air heating Combi 4 G/E incl. digital control unit	X		
Digital control panel for Combi heating (G/E only)	Х	Х	
Electric Autonomy equipment	Х	Х	х
Fresh water tank 70 l	Х	Х	Х
Hot air heating Combi 6 G/E incl. digital control unit		Х	
Additional weight (kg)*	55.5	55.5	40.5

Safety Package (8950)

ATC Trailer Control

DuoControl safety gas pressure regulator with crash sensor and EisEx gas regulator heater

Smoke detector

Additional weight (kg)*

Shower Package (6105)

Shower equipment with shower fittings and curtain

City water connection

Additional weight (kg)*

7

 \triangle Not known at the time of publication



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the payload. The specified additional weight for packages and optional equipment shows the additional weight compared with the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the mass for optional equipment specified by the manufacturer in the model overviews. This is an imputed

Optional equipment*	Included in package	Additional weight (kg)*	Code	460 EL	500 QSK	510 LE	530 FSK	540 QMK	550 ESK	560 FMK	730 FKR
Chassis											
17" alloy wheels in Dethleffs design (single axle)		10	11608	0	0	0	0	0	0	0	_
17" alloy wheels in Dethleffs design (tandem axle)	_	0	11609	_	-	-	-	-	-	-	0
Tyres on alloy wheels 185 R14 C LI102, up to and including 1600 kg		0	836	0	0	0	0	_	0	_	_
Tyres on alloy wheels 185/70 R14 L188, up to and including 2000 kg	_	0	840	_	-	-	-	_	-	-	0
Tyres on alloy wheels 195 R14 C LI106, 1700 kg and 1800 kg		2	838	0	0	0	0	0	0	0	_
Tyres on alloy wheels 195/70 R14 C L1104, 2200 kg to 2800 kg	_	4	859	_	-	-	-	_	_	_	0
Weight upgrade											
Weight upgrade 1.700 kg (incl. steel wheel 195 R14 C LI106)	_	23.1	278	0	_	_	_	_	_	_	_
Weight upgrade 1.700 kg (incl. steel wheel 195 R14 C LI106)	_	23.9	278	_	0	_	_	_	_	_	_
Weight upgrade 1.700 kg (incl. steel wheel 195 R14 C LI106)	_	24.3	278	_	_	0	_	_	_	_	_
Weight upgrade 1.700 kg (incl. steel wheel 195 R14 C LI106)	_	0.3	278	_	_	_	0	_	0	_	_
Weight upgrade 1.800 kg (incl. steel wheel 195 R14 C LI106)	_	5.9	279	_	_	_	_	0	_	_	_
Weight upgrade 1.800 kg (incl. steel wheel 195 R14 C LI106)	_	6.8	279	_	_	_	0	_	0	_	_
Weight upgrade 1.800 kg (incl. steel wheel 195 R14 C LI106)	_	6.6	279	_	_	_	_	_	_	0	_
Weight upgrade 1.800 kg (incl. steel wheel 195 R14 C LI106)	_	31.6	279	_	0	_	_	_	_	_	_
Weight upgrade 1.800 kg (incl. steel wheel 195 R14 C LI106)	_	32	279	_	_	0	_	_	_	_	_
Weight upgrade 1.900 kg (incl. alloy wheel 225/70 R15 C LI112)	_	18.7	394	_	_	_	_	_	_	0	_
Weight upgrade 1.900 kg (incl. alloy wheel 225/70 R15 C LI112)	_	19.2	394	_	_	_	0	_	0	_	_
Weight upgrade 1.900 kg (incl. alloy wheel 225/70 R15 C LI112)	_	23.8	394	_	_	_	_	0	_	_	_
Weight upgrade 2.000 kg (incl. alloy wheel 225/70 R15 C LI112)	_	23.8	138	_	_	_	_	0	_	_	_
Weight upgrade 2.000 kg (incl. alloy wheel 225/70 R15 C LI112)	_	19.2	138	_	_	_	0	_	0	_	_
Weight upgrade 2.000 kg (incl. alloy wheel 225/70 R15 C LI112)	_	18.7	138	_	_	_	_	_	_	0	_
Weight upgrade 2.200 kg (incl. steel wheel 195/70 R14 C LI104)	_	2.6	6351	_	_	_	_	_	_	_	0
Weight upgrade 2.500 kg (incl. steel wheel 195/70 R14 C LI104)	_	2.6	496	_	_	_	_	_	_	_	0
Weight upgrade to 1.600 kg	_	23.6	322	_	0	_	_	_	_	_	_
Weight upgrade to 1.600 kg	_	22.8	322	0	-	_	_	_	_	_	_
Weigth upgrade 2.800 kg (incl. steel wheel 195/70 R14 C LI104)		27.4	7713	_	_	_	_	_	_	_	0
Chassis features											
ATC Trailer Control	_	4	748	0	0	0	0	0	0	0	0
Breakdown kit	_	1	620	0	0	0	0	0	0	0	0
Draw bar cover	_	2	434	0	0	0	0	0	0	0	0
Large support feet, 4 pc.	_	1	6348	0	0	0	0	0	0	0	0
Solid rubber support wheel with support load indicator	_	2	10063	0	0	0	0	0	0	0	0
Spare tyre with alloy wheel 185 R14 C LI 102, up to and including 1.600 kg	_	17	837	0	0	0	_	_	_	_	_
Spare tyre with alloy wheel 185/70 R14 LI 88, up to and including 2.000 kg	_	18	841	_	_	_	_	_	_	_	0
Spare tyre with alloy wheel 195 R14 C 8PR-LI 106, 1.700 kg and 1.800 kg	_	19	839	0	0	0	_	_	_	0	_
Spare tyre with alloy wheel 195/70 R14 C-LI 102, 2.200 kg to 2.800 kg	_	19	861	_	_	_	_	_	_	_	0
Spare tyre with alloy wheel 225/70 R15 C LI 112 , 1.900 kg and 2.000 kg	_	23.5	1092	_	_	_	_	_	_	0	_
Spare tyre with steel wheel 185 R14 C 8 PR, up to and including 1.600 kg	_	18	831	0	0	0	_	_	_	_	_
Spare tyre with steel wheel 185/70 R14 LI 88, up to and including 2.000 kg	_	18	835	_	-	_	_	_	_	_	0
Spare tyre with steel wheel 195 R14 C LI 106, 1.700 kg and 1.800 kg	_	19.5	833	0	0	0	_	_	_	0	_
Spare tyre with steel wheel 195/70 R14 C-LI 104, 2.200 kg to 2.800 kg	_	20	860	_	_	_	_	_	_	_	0



Optional equipment*	Included in package	Additional weight (kg)*	Code	460 EL	500 QSK	510 LE	530 FSK	540 QMK	550 ESK	560 FMK	730 FKR
Wheel trims for 14" tyres	_	2	276	0	0	0	0	0	0	0	0
Exterior features											
Cassette awning 3750x2500 mm, manual	_	25.5	6928	0	_	_	_	_	_	_	_
Cassette awning 4000x2500 mm, manual	_	27.5	6928	_	0	0	_	_	_	_	_
Cassette awning 4500x2500 mm, manual	_	30	6928	_	_	_	0	0	0	0	_
Cassette awning 6000x3000 mm, manual	_	54.6	6928	_	_	_	_	_	_	_	0
Flush-fitting windows (not possible for front and rear windows) 8)	_	3	7561	0	0	0	0	0	0	0	0
Front window	_	4	982	0	0		_	0	0	_	_
Front window (bed area), if washroom in front	_	5	855	_	_	_	0	_	_	0	0
One-piece habitation door with window	_	3	862	0	0	0	0	0	0	0	0
Rear window	_	4	1108	•	_	0	_	_	_	_	•
XPS insulation for front, rear and sides (depending on vehicle size)	_	17.6	179	0	_	_	_	_	_	_	_
XPS insulation for front, rear and sides (depending on vehicle size)	_	20.1	179	_	0	0	0	0	_	_	_
XPS insulation for front, rear and sides (depending on vehicle size)	_	22.8	179	_	_	_	_	_	0	0	_
XPS insulation for front, rear and sides (depending on vehicle size)	_	25	179	_	_	_	_	_	_	_	0
Exterior design											
Front moulding with high attachment and roof rails	_	1	627	0	0	0	0	0	0	0	0
Manoeuvring handles in chrome design	_	0	754	0	0	0	0	0	0	0	0
Rear light carrier with high attachment and roof rails	_	11	624	0	0	0	0	0	0	0	0
Smooth sides titanium silver metallic	_	18.7	659	0	_	_	_	_	_	_	_
Smooth sides titanium silver metallic	_	21.3	659	_	0	0	0	0	_	_	_
Smooth sides titanium silver metallic	_	24.1	659	_	_	_	_	_	0	0	_
Smooth sides titanium silver metallic	_	26.4	659	_	_	_	_	_	_	_	0
Smooth sides white	_	18.7	443	0	_	_	_	_	_	_	_
Smooth sides white	_	21.3	443	_	0	0	0	0	_	_	_
Smooth sides white	_	24.1	443	_	_	_	_	_	0	0	_
Smooth sides white	_	26.4	443	_	_	_	_	_	_	_	0
Access locker doors											
Access locker door 1550x1050 mm with window	_	8	9486	_	_	_	_	0	_	_	_
Access locker door front left 997x419 mm	_	2.2	1079	_	_	_	_	_	0		
Access locker door front left side 1069x299 mm	_	2	1083	_	_	0	_	_	_	_	_
Access locker door front left side 648x348 mm	_	2	1071	_	_	_	_		0	_	_
Access locker door front right side 1069x299 mm	_	2	1084	_	_	0	_	_	_	_	_
Access locker door rear left side 1069x299 mm	_	2	1085	_	_	_	_	_	_	_	0
Access locker door rear left side 749x297 mm	_	2	1077	0	_	_	_	_	_	_	_
Access locker door rear right side 1069x299 mm	_	2	1086	_	_	_	_	_	_	_	0
Access locker door rear right side 749x297 mm	_	2	1078	0	_	_	_	_	_	_	_
Interior design											
Upholstery Galaxy	_	0	11269	0	0	0	0	0	0	0	0
Upholstery Mount	_	0	11270	0	0	0	0	0	0	0	0
Textile equipment											
7-zones double bed mattress, made of heat-regulating material with watergel cover	-	4	8214	-	0	-	0	0	-	0	0



Optional equipment*	Included in package	Additional weight (kg)*	Code	460 EL	500 QSK	510 LE	530 FSK	540 QMK	550 ESK	560 FMK	730 FKR
7-zones mattress left side, made of heat-regulating material with watergel cover	_	2	8215	0	_	0	_	_	0	_	_
7-zones mattress right side, made of heat-regulating material with watergel cover	-	5	8216	0	_	0	-	_	0	-	-
Corner head rests for U-shaped seating lounge	_	2	9236	_	_	_	=	0	_	0	0
Loose carpet	_	8.5	513	0	0	0	0	0	0	0	0
Furniture layouts											
Bunk bed with 2 sleeping berths, not foldable, instead of seating lounge	_	0	9775	_	_	_	_	_	_	_	0
Bunk bed with 3 sleeping berths, not foldable	_	20	200	_	0	_	0	0	0	0	_
Single beds convert to double bed	_	5	685	0	_	0	_	_	0	_	_
Slatted bed frame with adjustable head section	_	1	871	0	_	0	_	_	0	_	
Interior features											
2 kg fire extinguisher	_	3.5	843	0	0	0	0	0	0	0	0
Smoke detector	_	0.5	8949	0	0	0	0	0	0	0	0
Kitchen											
Extractor fan	-	3	785	0	0	0	0	0	0	0	0
Kitchen unit with large fridge (175 l), separate freezer and electric ignition	_	18	429	_	_	_	_	_	_	_	0
Kitchen worktop extension, foldable	_	1	1107	_	_	_	_	_	_	_	0
Oven	_	17	572	0	0	0	0	0	0	0	0
Bathroom											
Bathroom in alternative design	_	4	604		_	_	0	_	_	0	0
Multimedia							Ė			Ť	
FS-SAT system Voyager 65 Digimatic	_	10	1049		0	0	0		0		0
Flat screen TV 22" incl. DVD player and receiver	_	3.5	1103	0	0	0	0	0	0	0	0
Multifunctional external connection, 12 V, 220 V, TV and SAT	_	1	611	0	0	0	0	0	0	0	0
Preparation for flat screen TV (antenna cable and TV bracket)	_	2	678	0	0	0	0	0	0	0	0
SAT parabol antenna flat 65 Easy 65 Twin	_	14	879	_	0	0	0	_	0	0	0
Heating											
Electric floor heating	_	9	387	0	0	0	0	0	0	0	0
Fan 12 V with automatic speed control for S 5004	_	2	178	_	_	_	0	0	0	0	0
Fan 12V for S 3004	_	2	177	0	0	0	_	_	_	_	_
Hot air heating Combi 4 G/E incl. digital control unit	_	15	10480	0	0	0	_	_	_	_	_
Hot air heating Combi 6 G/E incl. digital control unit	_	15	9427	_	_	_	0	0	0	0	0
Hot water floor heating (only in comb. with option 205) 9)	_	10	674	_	_	_	0	0	0	0	0
Hot water heating	_	40	205	_	_	_	0	0	0	0	0
Ultraheat additional heating for S 3004, electric 220 V	_	2	364	0	0	0	_	_	-	_	_
Ultraheat additional heating for S 5004, electric 220 V	_	2	422	_	_	_	0	0	0	0	0
Air Conditioning											
Pre-wiring for A/C	_	0	172	0	0	0	0	0	0	0	0
Roof A/C	_	35	8145	0	0	0	0	0	0	0	0
Electrical installation											
Electric Autonomy equipment	_	38	492	0	0	0	0	0	0	0	0



Optional equipment*	Included in package	Additional weight (kg)*	Code	460 EL	500 QSK	510 LE	530 FSK	540 QMK	550 ESK	560 FMK	730 FKR
Indirect lighting	_	2	633	0	0	0	0	0	0	0	0
Water supply											
City water connection	_	2	414	0	0	0	0	0	0	0	0
Exterior shower	_	2	396	0	0	0	0	0	0	0	0
Fresh water tank 70 l	_	2.5	592	0	0	0	0	0	0	0	0
Shower equipment with shower fittings and curtain	_	5	1097	0	0	0	0	0	0	0	0
Waste water pipes insulated and heated	_	5	520	0	0	0	0	0	0	0	0
Gas supply											
DuoControl safety gas pressure regulator with crash sensor and EisEx gas regulator heater	_	2.5	784	0	0	0	0	0	0	0	0
Gas socket (exterior)	_	1	187	0	0	0	0	0	0	0	0
Packages											
Mover Autonomy Package (single axle)	_	70	5560	0	0	0	0	0	0	0	_
Mover Autonomy Package (tandem axle)	_	98	5561	_	_	_	=	_	_	=	0
Safety Package	_	7	8950	0	0	0	0	0	0	0	0
Shower Package	_	7	6105	0	0	0	0	0	0	0	0
Styling Package silver (single axle)	_	51.1	13255	_	_	_	_	_	0	0	_
Styling Package silver (single axle)	_	48.3	13255	_	0	0	0	0	_	_	_
Styling Package silver (single axle)	_	45.7	13255	0	_	_	_	_	_	_	_
Styling Package silver (tandem axle 2.8 t)	_	47.4	13259	_	_	_	_	_	_	_	0
Styling Package silver (tandem axle)	_	43.4	13257	_	_	_	_	_	_	_	0
Styling Package white (single axle)	_	51.1	13254	_	_	_	_	_	0	0	_
Styling Package white (single axle)	_	48.3	13254	_	0	0	0	0	_	_	_
Styling Package white (single axle)	_	45.7	13254	0	_	_	_	_	_	_	_
Styling Package white (tandem axle 2.8 t)	_	47.4	13258	_	_	_	_	_	_	_	0
Styling Package white (tandem axle)		43.4	13256	_	_	_	_	_	_	_	0
Water & Electric Autonomy Package with Combi or hot water heating system	_	40.5	9943	0	0	0	0	0	0	0	0
Water and Electric Autonomy Package Combi 4		55.5	11031	0	0	0	_	_	_	_	_
Water and Electric Autonomy Package Combi 6	_	55.5	11032	_	_	_	0	0	0	0	0
Winter Comfort Package Combi 4		50.1	10479	_	0	0	Ξ	_	_	_	_
Winter Comfort Package Combi 4	_	47.6	10479	0	_	_	_	_	_	_	_
Winter Comfort Package Combi 6	_	52.8	9536	_	_	_	_	_	0	0	_
Winter Comfort Package Combi 6	_	55	9536	_		_	_	_	_		0
Winter Comfort Package Combi 6	_	50.1	9536	_	_	_	0	O		_	_
Winter Comfort Package SNOW	_	79	5459	_	_	_	_	_	_	_	O
Winter Comfort Package SNOW	_	76.8	5459				_	_	0	0	
Winter Comfort Package SNOW		74.1	5459				0	0	_	_	
Winter Comfort Package SNOW PLUS Winter Comfort Package SNOW PLUS	_	77.8 80	5551 5551			_	_			0	
Winter Comfort Package SNOW PLUS Winter Comfort Package SNOW PLUS	_	75.1	5551				0	0			
Miscellaneous		/3.1	اددد								
		^	15454				Î	١	۱	Ĺ	
Registration documents (CoC papers)	_	0	15151	•	•	•	•	•	•	•	•

O Optional equipment lacktriangle Not possible lacktriangle Standard equipment lacktriangle Mandatory Δ Not known at the time of publication



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the payload. The specified additional weight for packages and optional equipment shows the additional weight compared with the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the mass for optional equipment specified by the manufacturer in the model overviews. This is an imputed

value determined for each model and layout that Dethleffs uses to determine the maximum weight available for factory-installed optional equipment. In the event of an increase of load capacity, the mass for optional equipment specified by the manufacturer is increased. For detailed information and explanations on the topic of weight, please refer to the "Legal notes" section.

Nomad

Experience pays off

With its comprehensive equipment and stylish, detailed solutions, the Nomad is the perfect caravan for demanding travellers. One highlight is the sophisticated Light Moments lighting concept, which is stylishly designed for the ultimate feel-good mood - regardless of the weather!

Technical info Overall length, approx. 691 - 942 cm Overall width, approx. 230 - 250 cm Overall height, approx. 265 cm Headroom in living area, approx. 198 cm

Maximum values partly not possible for all models or only in connection with certain options.

Upholstery



+ Upholstery Ruby



+ Upholstery Champion O



+ Upholstery Chromo O

Plus factors

- + Something for everyone: a wide range of caravans with double and single-bed layouts
- Sophisticated exterior design: chic details such as a designer rear moulding with integrated lights, chrome trim on the side walls and chrome manoeuvring handles
- + Well-being atmosphere: exquisite, elegant living room design with atmospheric light concept
- + Cooking like at home: very well-equipped gourmet kitchen with illuminated kitchen back panel
- + Good as standard: ready to go thanks to comprehensive specifications



























Wood décor



- + Wood décor Noce Nagano
- O optionally available

Nomad Technical info









Nomad		460 EL	490 EST	510 LE	520 ELT
Standard chassis		Lightweight chassis, 1500 kg	Lightweight chassis, 1500 kg	Lightweight chassis, 1600 kg	Lightweight chassis, 1700 kg
Overall length, approx.	cm	691	729	762	762
Body length approx.	cm	550	590	630	630
Overall width, approx.	cm	230	230	230	250
Overall height, approx.	cm	265	265	265	265
Circumferential dimension awning approx.	cm	948	988	1028	1028
Headroom in living area, approx.	cm	198	198	198	198
Thickness floor / side walls / roof	mm	42 / 34 / 34	42 / 34 / 34	42 / 34 / 34	42 / 34 / 34
Tire size		185 R14C 8PR	185 R14C 8PR	185 R14C 8PR	195 R14C LI106
Bed dimension: Front bed, L x W, approx.	cm	200 x 85 / 190 x 85 / 190 x 210 O	200 x 85 / 190 x 85 / 190 x 210 O	210 x 135	200 x 85 / 190 x 85 / 190 x 210 O
Bed dimension: Central / middle bed, L X W, approx.	cm		185 x 90		185 x 90
Bed dimension: Rear bed, L x W, approx.	cm	210 x 115		2x 200 x 85 / 200 x 215 O	
Sleeping berths standard / max.		3	3	4	3
Mass in running order (+/-5%)*	kg	1275 (1211 to 1339)*	1325 (1259 to 1391)*	1380 (1311 to 1449)*	1490 (1416 to 1565)*
$\label{eq:mass} \mbox{Manufacturer-specified mass for optional equipment}^*$	kg	140	86	117	117
Technically permissible maximum laden mass*	kg	1500	1500	1600	1700
Heating		S 3004, 3.5 kW Gas / Combi 4 G/E, 4 kW Gas-Electric O	Combi 4 G/E, 4 kW Gas-Electric	S 3004, 3.5 kW Gas / Combi 4 G/E, 4 kW Gas-Electric O	Combi 6 G/E, 6 kW Gas-Electric / Hot water heating, 6.4 kW Gas-Electric O
Refrigerator volume (thereof freezer), approx.	1	137 (15)	137 (15)	137 (15)	137 (15)
Waste water tank, approx.	I	22	22	22	22
Fresh water tank capacity, total/ Fresh water tank capacity driving filling	at I	43 / 15	48 / 15	43 / 15	48 / 15
Sockets: 12 V / 230 V / USB		0/6/1	0/6/1	0/7/1	0/0/1



The specified mass in running order is a standard value defined in the type approval procedure. Due to manufacturing tolerances, the actual weighed mass in running order may deviate from the value stated above. Deviations of up to \pm 5% of the mass in running order are legally permissible and possible. The permissible range in kilograms is stated in parentheses after the mass in running order. The mass for optional equipment specified by the manufacturer is an imputed value determined for each type and layout by which Dethleffs specifies the maximum weight available for factory-fitted optional equipment. The purpose of limiting optional equipment is to ensure that the minimum payload, i.e. the legally required free mass for baggage and retrofitted accessories, is actually available for the load capacity of vehicles delivered by

Nomad Technical info









Nomad		530 DR	560 FMK	650 RQT	730 FKR
Standard chassis		Lightweight chassis, 1600 kg	Lightweight chassis, 1700 kg	Lightweight chassis, 2000 kg	Lightweight chassis, 2200 kg
Overall length, approx.	cm	788	818	872	942
Body length approx.	cm	650	675	735	805
Overall width, approx.	cm	230	250	250	250
Overall height, approx.	cm	265	265	265	265
Circumferential dimension awning approx.	cm	1048	1078	1138	1208
Headroom in living area, approx.	cm	198	198	198	198
Thickness floor / side walls / roof	mm	42 / 34 / 34	42 / 34 / 34	42 / 34 / 34	42 / 34 / 34
Tire size		185 R14C 8PR	195 R14C LI106	185/70 R14 LI88	195/70 R14C LI104
Bed dimension: Front bed, L x W, approx.	cm	205 x 150	200 x 155	230 x 155	200 x 155
Bed dimension: Central / middle bed, L X W, approx.	cm		230 x 115	200 x 155	200 x 75 / 2x 195 x 75 / 2x 195 x 75 〇
Bed dimension: Rear bed, L x W, approx.	cm	210 x 135	195 x 70 / 190 x 75 / 195 x 75 O / 195 x 80 O / 195 x 70 O		230 x 155
Sleeping berths standard / max.		4	5 / 6 🔿	4	7/80
Mass in running order (+/-5%)*	kg	1395 (1325 to 1465)*	1550 (1473 to 1628)*	1760 (1672 to 1848)*	1855 (1762 to 1948)*
$\label{eq:mass_period} \mbox{Manufacturer-specified mass for optional equipment}^*$	kg	100	33	127	195
Technically permissible maximum laden mass*	kg	1600	1700	2000	2200
Heating		S 5004, 6 kW Gas / Combi 6 G/E, 6 kW Gas-Electric O / Hot water heating, 6.4 kW Gas-Electric O	S 5004, 6 kW Gas / Combi 6 G/E, 6 kW Gas-Electric O / Hot water heating, 6.4 kW Gas-Electric O	S 5004, 6 kW Gas / Combi 6 G/E, 6 kW Gas-Electric O / Hot water heating, 6.4 kW Gas-Electric O	S 5004, 6 kW Gas / Combi 6 G/E, 6 kW Gas-Electric O / Hot water heating, 6.4 kW Gas-Electric O
Refrigerator volume (thereof freezer), approx.	1	137 (15)	137 (15)	137 (15)	86 (11) / 156 (29) 🔿
Waste water tank, approx.	I	22	22	22	22
Fresh water tank capacity, total/ Fresh water tank capacit driving filling	y at	43 / 15	43 / 15	43 / 15	43 / 15
Sockets: 12 V / 230 V / USB		0/9/1	0/9/3	0/9/1	0 / 10 / 3



The specified mass in running order is a standard value defined in the type approval procedure. Due to manufacturing tolerances, the actual weighed mass in running order may deviate from the value stated above. Deviations of up to \pm 5% of the mass in running order are legally permissible and possible. The permissible range in kilograms is stated in parentheses after the mass in running order. The mass for optional equipment specified by the manufacturer is an imputed value determined for each type and layout by which Dethleffs specifies the maximum weight available for factory-fitted optional equipment. The purpose of limiting optional equipment is to ensure that the minimum payload, i.e. the legally required free mass for baggage and retrofitted accessories, is actually available for the load capacity of vehicles delivered by

O Optional equipment — Not possible

Standard equipment

Mandatory

Not known at the time of publication

Classified 1968 RF4 C LI1046 (with steel wheel 1,2004 kg and 1,800 kg)	Standard equipment	460 EL	490 EST	510 LE	520 ELT	530 DR	560 FMK	650 RQT	730 FKR
Section Page									
Types on steel wheels 185 REA CS PR. Up to and including 1600 kg 1			_	_	•	_	•	_	_
Section Sect		_	_	_	_	_	_	_	
Classified chassis with inertia braking system with reversing automatic Classified chasses with inertia braking system with reversing automatic Classified chasses with inertia braking system with reversing automatic Classified chasses with inertia braking system with reversing automatic Classified chasses with inertia braking system with a reversible Classified chasses with inertia braking system with a reversible Classified chasses		•			_		_	_	_
Characterise Health and prake As admired prake As admired prake As sabilised Park Park Park Park Park Park Park Park		_	_	_	_	_	_		_
ACK self-adjusting brake		-	_	_	_	-	_	•	å
ACS stabiliser High-quality brand-name tyres, designed for a speed of 100 km/h High-quality brand-name and heat speed of 100 km/h High-quality brand-n									
Right-quality brand-name tyres, designed for a speed of 100 km/h Lightweight comes steadies		•	•	•	•	•	•	•	•
Lightweight comer steadies									
Categors shock absorber Categors Categ				•	•		•	•	
Proof the gas bottle locker made of rot-resistant and robust corrugated aluminium									
Flysteren door Floor Flysteren door Floor Fl		_	_	Ť	_	_	_		Š
Figure and or front parts in gas locker area made of LFI (long fiber injection) technology, shock resistant, robust and repair-friendly Figure 1 in gas locker area made of LFI (long fiber injection) technology, shock resistant, robust and repair-friendly Figure 1 in gas locker area made of LFI (long fiber injection) technology, shock resistant, robust and repair-friendly Figure 1 in gas locker area made of LFI (long fiber injection) technology, shock resistant, robust and repair-friendly Figure 1 in gas locker door with window One-pice habitation door with window One-pice habitation door with window Opening window in bathroom Opening windows, trapezoid, insulated and double-glazed (graphite grey) with blackout and mosquito blinds Opening windows, trapezoid, insulated and double-glazed (graphite grey) with blackout and mosquito blinds Opening windows, trapezoid, insulated and double-glazed (graphite grey) with blackout and mosquito blinds Opening windows, trapezoid, insulated and double-glazed (graphite grey) with blackout and mosquito blinds Opening windows, trapezoid, insulated and double-glazed (graphite grey) with blackout and mosquito blinds Opening windows, trapezoid, insulated and double-glazed (graphite grey) with blackout and mosquito blinds Opening window in bathroom Agone Windows, trapezoid, insulated and double-glazed (graphite grey) with blackout and mosquito blinds Opening window in bathroom Agone Windows, trapezoid, insulated and double-glazed (graphite grey) with blackout and mosquito blinds Opening window in bathroom Agone Windows, trapezoid, insulated and double-glazed (graphite grey) with blackout and mosquito blinds of Windows Agone Opening windows trapezoid, insulated and double-glazed (graphite grey) with blackout and mosquito blinds of Windows Agone Opening windows Agone Op									
Front parts in gas locker area made of LFI (long fiber injection) technology, shock resistant, robust and repair-firednyly fully-inculated wheel houses Midd Hekli Iffrach'lit skylight ind. illuminated roof lining One-piece habitation door with window Opening window in bathroom		•	•	•	•	•		•	
Fully insulated wheel houses Midd Held lift- and-filt skylight ind. illuminated roof lining One-piece habitation door with window Opening window in bathroom Opening window in bathroom Opening window, trapezoid, insulated and double-glazed (graphite grey) with blackout and mosquito blinds Opening windows, trapezoid, insulated and double-glazed (graphite grey) with blackout and mosquito blinds Opening windows, trapezoid, insulated and double-glazed (graphite grey) with blackout and mosquito blinds Opening windows, trapezoid, insulated and double-glazed (graphite grey) with blackout and mosquito blinds Opening windows, trapezoid, insulated and double-glazed (graphite grey) with blackout and mosquito blinds Opening windows, trapezoid, insulated and double-glazed (graphite grey) with blackout and mosquito blinds Opening windows, trapezoid, insulated and double-glazed (graphite grey) with blackout and mosquito blinds Opening windows, trapezoid, insulated and double-glazed (graphite grey) with blackout and mosquito blinds Opening windows, trapezoid, insulated and double-glazed (graphite grey) with blackout and mosquito blinds Opening windows, trapezoid, insulated and double-glazed (graphite grey) with blackout and mosquito blinds Opening windows, trapezoid, insulated and double-glazed (graphite grey) with blackout and mosquito blinds Opening windows, trapezoid, insulated and suble-glazed (graphite grey) with blackout and mosquito blinds Opening windows, trapezoid, insulated and suble-glazed (graphite grey) with blackout and mosquito blinds Opening windows, trapezoid, insulated and suble-glazed (graphite grey) with blackout and mosquito blinds Opening windows, trapezoid, insulated and suble-glazed (graphite grey) with blackout and mosquito blinds Opening windows, trapezoid, insulated and suble-glazed (graphite grey) with blackout and mosquito blinds Opening windows trapezoid, insulated and suble-glazed (graphite grey) with blackout and mosquite grey and suble grey and suble grey and suble grey and									
Midi Heki lift-and-tilt skylight incl. illuminated roof linining One-pice habitation door with window One-pice habitation door with window One-pice habitation door with window Opening window in bathroom Opening windows, trapezoid, insulated and double-glazed (graphite grey) with blackout and mosquito blinds Robust GRP roof Sidewall skirts with integrated side-marker lamps Sidewall skirts with integrated side-marker lamps Space-saving gas locker door which opens upwards Space space for 2 gas bottles with 11 kg filling weight each Peterior design Front and rear in smooth sides white Manoeuvring handles in chrome design Sides in hammer finish, white Access locker door front right side 648x348 mm Access locker door front right side 997x419 mm Access locker door front right side 997x419 mm Access locker door rear right side 997x419 mm Access locker door rear right side 997x419 mm Access locker door front Roor Roor Roor Roor Roor Roor Roor Roo						•	•	•	
One-piece habitation door with window									
Opening window in bathroom - </td <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>									
Opening windows, trapezoid, insulated and double-glazed (graphite grey) with blackout and mosquito blinds 0									
Robust GRP roof 0	, 3								
Skylight Mini Heki 0			•		•		•	•	•
Skylight Mini Heki 0	Sidewall skirts with integrated side-marker lamps		•	•	•	•	•	•	•
Spare wheel carrier in gas locker Image: Space for 2 gas bottles with 11 kg filling weight each Image: Space for 2 gas bottles with 11 kg filling weight each Image: Space for 2 gas bottles with 11 kg filling weight each Image: Space for 2 gas bottles with 11 kg filling weight each Image: Space for 2 gas bottles with 11 kg filling weight each Image: Space for 2 gas bottles with 11 kg filling weight each Image: Space for 2 gas bottles with 11 kg filling weight each Image: Space for 2 gas bottles with 11 kg filling weight each Image: Space for 2 gas bottles with 11 kg filling weight each Image: Space for 2 gas bottles with 11 kg filling weight each Image: Space for 2 gas bottles with 11 kg filling weight each Image: Space for 2 gas bottles with 11 kg filling weight each Image: Space for 2 gas bottles with 12 kg filling weight each Image: Space for 2 gas bottles with 12 kg filling weight each Image: Space for 2 gas bottles with 12 kg filling weight each Image: Space for 2 gas bottles with 12 kg filling weight each Image: Space for 2 gas bottles with 12 kg filling weight each Image: Space for 2 gas bottles with 12 kg filling weight each Image: Space for 2 gas bottles with 12 kg filling weight each Image: Space for 2 gas bottles with 12 kg filling weight each Image: Space for 2 gas bottles with 12 kg filling weight each Image: Space for 2 gas bottles with 12 kg filling weight each Image: Space for 2 gas bottles weight each		•	•	•	•	•	•	•	•
Storage space for 2 gas bottles with 11 kg filling weight each Storage space for 2 gas bottles with 11 kg filling weight each Storage space for 2 gas bottles with 11 kg filling weight each Storage space for 2 gas bottles with 12 kg filling weight each Storage space for 2 gas bottles with 12 kg filling weight each Storage space for 2 gas bottles white Storage space for 2 gas bottles Storage space for 2 gas	Space-saving gas locker door which opens upwards								
Exterior design Front and rear in smooth sides white Image: content of the property o	Spare wheel carrier in gas locker	•	•	•	•	•	•	•	•
Front and rear in smooth sides white Manoeuvring handles in chrome design Sides in hammer finish, white Access locker doors Access locker door front right side 648x348 mm Access locker door front right side 648x348 mm Access locker door front right side 997x419 mm Access locker door rear right side	Storage space for 2 gas bottles with 11 kg filling weight each	•	•	•	•	•	•	•	
Manoeuvring handles in chrome design Image: Manage of the properties of the prop	Exterior design								
Sides in hammer finish, white Image: Market Ma	Front and rear in smooth sides white	•	•	•	•	•	•	•	•
Access locker doors Access locker door front right side 648x348 mm	Manoeuvring handles in chrome design	•	•	•	•	•	•	•	•
Access locker door front right side 648x348 mm Access locker door front right side 997x419 mm Access locker door rear right side 997x419 mm Access locker door front right side 997x419 mm Access locker door for 10 mm Acces locker door locker doo	Sides in hammer finish, white					•		•	
Access locker door front right side 997x419 mm • • • • • • • • • • • • • • • • • • •	Access locker doors								
Access locker door front right side 997x419 mm • • • • • • • • • • • • • • • • • • •	Access locker door front right side 648x348 mm	_	_		_	•			
Access locker door rear right side997x419 mm Interior design Upholstery Ruby Wood décor Noce Nagano Textile equipment 7-zones double bed mattress, made of heat-regulating material 7-zones mattress left side, made of heat-regulating material 7-zones mattress right side, made of heat-regulating material 7-zones mattress right side, made of heat-regulating material 8		•	•	_	•	_	_	_	_
Upholstery Ruby Wood décor Noce Nagano Textile equipment 7-zones double bed mattress, made of heat-regulating material 7-zones mattress left side, made of heat-regulating material 7-zones mattress right side, made of heat-regulating material 7-zones mattress right side, made of heat-regulating material 8	-	_	_		_	_	_	•	_
Upholstery Ruby Wood décor Noce Nagano Textile equipment 7-zones double bed mattress, made of heat-regulating material 7-zones mattress left side, made of heat-regulating material 7-zones mattress right side, made of heat-regulating material 7-zones mattress right side, made of heat-regulating material 8	Interior design								
Wood décor Noce Nagano Textile equipment 7-zones double bed mattress, made of heat-regulating material 7-zones mattress left side, made of heat-regulating material 7-zones mattress right side, made of heat-regulating material 7-zones mattress right side, made of heat-regulating material 6			•	•	•	•	•		
Textile equipment 7-zones double bed mattress, made of heat-regulating material 7-zones mattress left side, made of heat-regulating material 7-zones mattress right side, made of heat-regulating material 7-zones mattress right side, made of heat-regulating material 8		•	•	•	•	•	•	•	•
7-zones double bed mattress, made of heat-regulating material									
7-zones mattress left side, made of heat-regulating material 7-zones mattress right side, made of heat-regulating material AirPlus - perfect air circulation in the interior and rear ventilation of the overhead lockers and sideboards Bunk bed with 2 sleeping berths, foldable Bunk bed with 2 sleeping berths, not foldable Bunk beds with safety net and ladder 7-zones mattress left side, made of heat-regulating material 8		_	_	_	_				
7-zones mattress right side, made of heat-regulating material Furniture layouts AirPlus - perfect air circulation in the interior and rear ventilation of the overhead lockers and sideboards Bunk bed with 2 sleeping berths, foldable Bunk bed with 2 sleeping berths, not foldable Bunk beds with safety net and ladder The provided Heat-regulating material The provi						_	_		
Furniture layouts AirPlus - perfect air circulation in the interior and rear ventilation of the overhead lockers and sideboards Bunk bed with 2 sleeping berths, foldable Bunk bed with 2 sleeping berths, not foldable Bunk beds with safety net and ladder Bunk beds with safety net and ladder						_	_	_	_
AirPlus - perfect air circulation in the interior and rear ventilation of the overhead lockers and sideboards Bunk bed with 2 sleeping berths, foldable Bunk bed with 2 sleeping berths, not foldable Bunk beds with safety net and ladder Description:			Ť	Ť	Ť				
Bunk bed with 2 sleeping berths, foldable Bunk bed with 2 sleeping berths, not foldable Bunk beds with safety net and ladder									
Bunk bed with 2 sleeping berths, not foldable Bunk beds with safety net and ladder									
Bunk beds with safety net and ladder $ -$			_	_	_				
		_	_	_	_	_		_	
One-legged telescopic table, height adjustable — — — • • • • •	One-legged telescopic table, height adjustable		_						•
Seating lounge converts to bed					•	•		•	
Special slatted frame with flexible natural rubber holders, opening for optimal use of storage compartments under the								•	
beds									

Standard equipment 490 EST 520 ELT 530 DR 460 EL 510 LE Kitchen Generous drawers with soft closing for absolutely silent closing Kitchen worktop with indirect lighting Large fridge with 137 liters capacity and 15 liters freezer compartment Practical 3-flames cooker with electric ignition Practical apothecary drawers (depending on layout) Spacious fridge with 86-litre volume and 11 litre freezer Bathroom Integrated design washbasin made of solid surface material Shower tray Skylight with mosquito net Heating Gas heating S 3004 with automatic ignition Gas heating S 5004 with automatic ignition • • • Hot air system **Electrical installation** 12 V power supply throughout vehicle Awning light 12V CEE external output socket for 230V on-board electrics Compact power distribution unit with 230V safety device and 12V fuse box in wardrobe incl. powerful 340W transformer Illuminated kitchen back panel Indirect lighting LED light bar system 12V (on head-side of bed and in seating lounge) USB port for spotlight bar Water supply Electric water supply Fresh water tank 38 l Hot water supply

Mobile 22 I waste water tank

Packages Nomad

Package	Styling Package white (single axle) (13254)	Styling Package white (single axle) (13254)	Styling Package white (single axle) (13254)	Styling Package white (tandem axle) (13256)	Styling Package white (tandem axle) (13256)	Styling Package white (tandem axle 2.8 t) (13258)
Smooth sides white	Х					
17" alloy wheels in Dethleffs design (single axle)	Х	Х	Х			
Draw bar cover	Х	Х	Х	x	Х	x
Large support feet, 4 pc.	Х	х	Х	x	Х	х
Solid rubber support wheel with support load indicator	Х	х	Х	x	Х	х
Manoeuvring handles in chrome design	Х	Х	Х	X	Х	х
Rear light carrier with high attachment and roof rails	Х	Х	Х	x	Х	x
Front moulding with high attachment and roof rails	Х	Х	Х	x	Х	x
Smooth sides white		х				
Smooth sides white			Х	X		
17" alloy wheels in Dethleffs design (tandem axle)				x	Х	
Smooth sides white					х	x
Tyres on alloy wheels 195/70 R14 C L1104, 2200 kg to 2800 kg						х
Additional weight (kg)*	45.7	48.3	51.1	41.1	43.4	47.4



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the payload. The specified additional weight for packages and optional equipment shows the additional weight compared with the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the mass for optional equipment specified by the manufacturer in the model overviews. This is an imputed

Package	Styling Package silver (single axle) (13255)	Styling Package silver (single axle) (13255)	Styling Package silver (single axle) (13255)	Styling Package silver (tandem axle) (13257)	Styling Package silver (tandem axle) (13257)	Styling Package silver (tandem axle 2.8 t) (13259)
Smooth sides titanium silver metallic	Х					
17" alloy wheels in Dethleffs design (single axle)	Х	х	х			
Draw bar cover	Х	Х	х	X	х	x
Large support feet, 4 pc.	Х	х	х	х	х	х
Solid rubber support wheel with support load indicator	Х	Х	х	X	х	x
Manoeuvring handles in chrome design	Х	х	х	x	х	х
Rear light carrier with high attachment and roof rails	Х	Х	х	Х	х	х
Front moulding with high attachment and roof rails	Х	Х	х	Х	х	х
Smooth sides titanium silver metallic		х				
Smooth sides titanium silver metallic			х	х		
17" alloy wheels in Dethleffs design (tandem axle)				х	х	
Smooth sides titanium silver metallic					х	х
Tyres on alloy wheels 195/70 R14 C LI104, 2200 kg to 2800 kg						Х
Additional weight (kg)*	45.7	48.3	51.1	41.1	43.4	47.4

Package	Winter Comfort Package Combi 4 (10479)	Winter Comfort Package Combi 4 (10479)	Winter Comfort Package Combi 6 (9536)	Winter Comfort Package Combi 6 (9536)	Winter Comfort Package Combi 6 (9536)	Winter Comfort Package for Combi heating (10481)
Digital control panel for Combi heating (G/E only)	Х	Х	Х	Х	Х	
Electric floor heating	Х	Х	х	Х	х	x
Waste water pipes insulated and heated	Х	Х	х	Х	х	x
Insulated threader hose	Х	Х	х	Х	х	x
XPS insulation for front, rear and sides (depending on vehicle size)	Х					
Hot air heating Combi 4 G/E incl. digital control unit	Х	Х				
XPS insulation for front, rear and sides (depending on vehicle size)		Х	х			x
Hot air heating Combi 6 G/E incl. digital control unit			х	Х	х	
XPS insulation for front, rear and sides (depending on vehicle size)				Х		
XPS insulation for front, rear and sides (depending on vehicle size)					Х	
Additional weight (kg)*	47.6	50.1	50.1	52.8	55	35.1



Package	Winter Comfort Package SNOW (5459)	Winter Comfort Package SNOW (5459)	Winter Comfort Package SNOW (5459)	Winter Comfort Package SNOW PLUS (5551)	Winter Comfort Package SNOW PLUS (5551)	Winter Comfort Package SNOW PLUS (5551)
Hot water heating	Х	Х	Х	Х	Х	х
Electric floor heating	Х	Х	Х			
Waste water pipes insulated and heated	Х	Х	Х	х	х	х
XPS insulation for front, rear and sides (depending on vehicle size)	Х			х		
XPS insulation for front, rear and sides (depending on vehicle size)		Х			х	
XPS insulation for front, rear and sides (depending on vehicle size)			Х			х
Hot water floor heating (only in comb. with option 205)				х	х	х
Additional weight (kg)*	74.1	76.8	79	75.1	77.8	80

Package	Mover Autonomy Package (single axle) (5560)	Mover Autonomy Package (tandem axle) (5561)
Mover manoeuvring support for single-axle	X	
Electric Autonomy equipment	X	X
Mover manoeuvring support for tandem-axle		X
Additional weight (kg)*	70	98

Package	Water and Electric Autonomy Package Combi 4 (11031)	Water and Electric Autonomy Package Combi 6 (11032)	Water & Electric Autonomy Package with Combi or hot water heating system (9943)
Hot air heating Combi 4 G/E incl. digital control unit	Х		
Digital control panel for Combi heating (G/E only)	Х	X	
Electric Autonomy equipment	Х	X	х
Fresh water tank 70 l	Х	X	х
Hot air heating Combi 6 G/E incl. digital control unit		Х	
Additional weight (kg)*	55.5	55.5	40.5

Safety Package (8950)

ATC Trailer Control

DuoControl safety gas pressure regulator with crash sensor and EisEx gas regulator heater

Smoke detector

Additional weight (kg)*

Shower Package (6105)

Shower equipment with shower fittings and curtain

City water connection

Additional weight (kg)

△ Not known at the time of publication



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the payload. The specified additional weight for packages and optional equipment shows the additional weight compared with the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the mass for optional equipment specified by the manufacturer in the model overviews. This is an imputed

Optional equipment*	Included in package	Additional weight (kg)*	Code	460 EL	490 EST	510 LE	520 ELT	530 DR	560 FMK	650 RQT	730 FKR
Chassis											
17" alloy wheels in Dethleffs design (single axle)	_	10	11608	0	0	0	0	0	0	_	_
17" alloy wheels in Dethleffs design (tandem axle)	_	0	11609	_	_	_	_	_	_	0	0
Tyres on alloy wheels 185 R14 C LI102, up to and including 1600 kg	_	0	836	0	0	0	_	0	_	_	_
Tyres on alloy wheels 185/70 R14 L188, up to and including 2000 kg	_	0	840	_	_	_	_	_	_	0	_
Tyres on alloy wheels 195 R14 C LI106, 1700 kg and 1800 kg	_	2	838	0	0	0	0	0	0	_	_
Tyres on alloy wheels 195/70 R14 C LI104, 2200 kg to 2800 kg	_	4	859	_	_	_	_	_	_	0	0
Weight upgrade											
Weight upgrade 1.700 kg (incl. steel wheel 195 R14 C LI106)	_	24	278	0	0	_	-	0	-	-	_
Weight upgrade 1.700 kg (incl. steel wheel 195 R14 C LI106)	_	0.3	278	_	_	0	_	_	_	_	_
Weight upgrade 1.800 kg (incl. steel wheel 195 R14 C LI106)	_	31.6	279	_	_	_	0	_	_	_	_
Weight upgrade 1.800 kg (incl. steel wheel 195 R14 C LI106)	_	27	279	_	0	_	_	0	0	_	_
Weight upgrade 1.800 kg (incl. steel wheel 195 R14 C LI106)	_	8	279	_	_	0	_	_	_	_	_
Weight upgrade 1.900 kg (incl. alloy wheel 225/70 R15 C LI112)	_	27	394	_	_	_	0	0	0	_	_
Weight upgrade 2.000 kg (incl. alloy wheel 225/70 R15 C LI112)	_	27	138	_	_	_	0	0	0	_	_
Weight upgrade 2.200 kg (incl. steel wheel 195/70 R14 C LI104)	_	1.5	6351	_	_	_	_	_	_	0	_
Weight upgrade 2.500 kg (incl. steel wheel 195/70 R14 C LI104)	_	1.5	496	_	_	_	_	_	_	0	_
Weight upgrade 2.500 kg (incl. steel wheel 195/70 R14 C LI104)	_	0	496	_	_	_	_	_	_	_	0
Weight upgrade to 1.600 kg	_	24	322	0	0	_	_	_	_	_	_
Weigth upgrade 2.800 kg (incl. steel wheel 195/70 R14 C LI104)	_	24.9	7713	_		_	_	_	_	_	0
Chassis features											
ATC Trailer Control	_	4	748	0	0	0	0	0	0	0	0
Breakdown kit	_	1	620	0	0	0	0	0	0	0	0
Draw bar cover	_	2	434	0	0	0	0	0	0	0	0
Large support feet, 4 pc.	_	1	6348	0	0	0	0	0	0	0	0
Solid rubber support wheel with support load indicator	_	2	10063	0	0	0	0	0	0	0	0
Spare tyre with alloy wheel 185 R14 C LI 102, up to and including 1.600 kg	_	17	837	0	0	0	_	0	_	_	_
Spare tyre with alloy wheel 185/70 R14 LI 88, up to and including 2.000 kg	_	18	841	_	_	_	_	_	_	0	_
Spare tyre with alloy wheel 195 R14 C 8PR-LI 106, 1.700 kg and 1.800 kg	_	19	839	0	0	0	0	0	0	_	_
Spare tyre with alloy wheel 195/70 R14 C-LI 102, 2.200 kg to 2.800 kg	_	19	861	_	_	_	_	_	_	0	0
Spare tyre with alloy wheel 225/70 R15 C LI 112 , 1.900 kg and 2.000 kg	_	23.5	1092	_	_	_	0	_	0	_	_
Spare tyre with steel wheel 185 R14 C 8 PR, up to and including 1.600 kg	_	18	831	0	0	0	_	0	_	_	_
Spare tyre with steel wheel 185/70 R14 LI 88, up to and including 2.000 kg	_	18	835	_	_	_	_	_	_	0	_
Spare tyre with steel wheel 195 R14 C LI 106, 1.700 kg and 1.800 kg	_	19.5	833	0	0	0	0	0	0	_	_
Spare tyre with steel wheel 195/70 R14 C-LI 104, 2.200 kg to 2.800 kg	_	20	860	_	_	_	_	_	_	0	0
Wheel trims for 14" tyres	_	2	276	0	0	0	0	0	0	0	0
Exterior features											
Cassette awning 3750x2500 mm, manual	_	25.5	6928	0		_					_
Cassette awning 4000x2500 mm, manual	_	27.5	6928	_	0	0	0	_	_	_	_
Cassette awning 4500x2500 mm, manual	_	30	6928	_	_	_	_	0	0	_	_
Cassette awning 5500x3000 mm, manual	_	50.6	6928	_	_	_	_	_	_	0	_
Cassette awning 6000x3000 mm, manual	_	54.6	6928	_	_	_	_	_	_	_	0
Flush-fitting windows (not possible for front and rear windows) 8)	_	3	7561	0	0	0	0	0	0	0	0
Front window	-	4	982	0	0	•	0	0	-	•	_



value determined for each model and layout that Dethleffs uses to determine the maximum weight available for factory-installed optional equipment. In the event of an increase of load capacity, the mass for optional equipment specified by the manufacturer is increased. For detailed information and explanations on the topic of weight, please refer to the "Legal notes" section.

Optional equipment*	Included in package	Additional weight (kg)*	Code	460 EL	490 EST	510 LE	520 ELT	530 DR	560 FMK	650 RQT	730 FKR
Front window (bed area), if washroom in front	_	5	855	_	_	_	_	_	0	_	0
Rear window	_	4	1108	•	_	0	_	•	_	_	•
XPS insulation for front, rear and sides (depending on vehicle size)	_	17.6	179	0	_	_	_	_	_	_	_
XPS insulation for front, rear and sides (depending on vehicle size)	_	20.1	179	_	0	0	0	0	_	0	_
XPS insulation for front, rear and sides (depending on vehicle size)	_	22.8	179	_	_	_	_	_	0	_	_
XPS insulation for front, rear and sides (depending on vehicle size)	_	25	179	_	_	_	_	_	_	_	0
Exterior design											
Front moulding with high attachment and roof rails	-	1	627	0	0	0	0	0	0	0	0
Rear light carrier with high attachment and roof rails	_	11	624	0	0	0	0	0	0	0	0
Smooth sides titanium silver metallic	_	18.7	659	0	_	_	_	_	_	_	_
Smooth sides titanium silver metallic	_	21.3	659	_	0	0	0	0	_	_	_
Smooth sides titanium silver metallic	_	24.1	659	_	_	_	_	_	0	0	_
Smooth sides titanium silver metallic	_	26.4	659	_	_	_	_	_	_	_	0
Smooth sides white	_	18.7	443	0	_	_	_	_	_	_	_
Smooth sides white	_	21.3	443	_	0	0	0	0	_	_	_
Smooth sides white	_	24.1	443	_	_	_	_	_	0	0	_
Smooth sides white	_	26.4	443	_	_	_	_	_	_	_	0
Access locker doors											
Access locker door front left 997x419 mm	_	2.2	1079	_	_	_	0	_		_	•
Access locker door front left side 1069x299 mm	_	2	1083	_	_	0	_	_	_	_	_
Access locker door front left side 648x348 mm	_	2	1071	_	_	_	0	0	_	_	_
Access locker door front right side 1069x299 mm	_	2	1084	_	_	0	_	_	_	0	_
Access locker door rear left side 1069x299 mm	_	2	1085	_	_	_	-	_	_	_	0
Access locker door rear left side 749x297 mm		2	1077	0	_	_	_	_	_	_	_
Access locker door rear right side 1069x299 mm	_	2	1086	_	_	_	_	0	_	_	0
Access locker door rear right side 749x297 mm	_	2	1078	0	_	_	_	_	_	_	_
Interior design											
Upholstery Champion	_	0	10489	0	0	0	0	0	0	0	0
Upholstery Chromo	_	0	10488	0	0	0	0	0	0	0	0
Textile equipment											
7-zones double bed mattress, made of heat-regulating material with watergel cover	_	4	8214	_	_	_	_	0	0	0	0
7-zones mattress left side, made of heat-regulating material with watergel cover	_	2	8215	0	0	0	0	_	_	_	_
7-zones mattress right side, made of heat-regulating material with watergel cover	_	5	8216	0	0	0	0	_	_	-	-
Corner head rests for U-shaped seating lounge	_	2	9236	_	_	_	_	0	0	0	0
Loose carpet	_	8.5	513	0	0	0	0	0	0	0	0
Furniture layouts											
Bunk bed with 2 sleeping berths, not foldable, instead of seating lounge	_	0	9775	-	-	-	-	-	-	-	0
Bunk bed with 3 sleeping berths, not foldable	_	20	200	_	_	_	_	_	0	_	_
1 3 '											
Single beds convert to double bed	_	5	685	0	0	0	0	_	_	_	_



Optional equipment*	Included in package	Additional weight (kg)*	Code	460 EL	490 EST	510 LE	520 ELT	530 DR	560 FMK	650 RQT	730 FKR
2 kg fire extinguisher	_	3.5	843	0	0	0	0	0	0	0	0
Smoke detector	_	0.5	8949	0	0	0	0	0	0	0	0
Kitchen											
Extractor fan	_	3	785	0	0	0	0	0	0	0	0
Kitchen unit with large fridge (175 l), separate freezer and electric ignition	_	18	429	_	_	_	_	_	_	_	0
Kitchen worktop extension, foldable	_	1	1107	_	_	_	_	_	_	0	0
Oven		17	572	0	0	0	0	0	0	0	0
Bathroom											
Bathroom in alternative design	_	4	604	_	_	_	_	_	0	_	0
Multimedia											
FS-SAT system Voyager 65 Digimatic	_	10	1049	_	0	0	0	_	_	0	0
Flat screen TV 22" incl. DVD player and receiver	_	3.5	1103	0	0	0	0	0	0	0	0
Multifunctional external connection, 12 V, 220 V, TV and SAT	_	1	611	0	0	0	0	0	0	0	0
Preparation for flat screen TV (antenna cable and TV bracket)	_	2	678	0	0	0	0	0	0	0	0
SAT parabol antenna flat 65 Easy 65 Twin	_	14	879	_	0	0	0	_	0	0	0
TV preparation in sleeping area	_	2	9360	_	_	_	_	_	_	0	_
Heating											
Electric floor heating	_	9	387	0	0	0	0	0	0	0	0
Fan 12 V with automatic speed control for S 5004	_	2	178	_	_	_	_	0	0	0	0
Fan 12V for S 3004	_	2	177	0	_	0	_	_	_	_	_
Hot air heating Combi 4 G/E incl. digital control unit	_	15	10480	0		0	_	_	_	_	_
Hot air heating Combi 6 G/E incl. digital control unit	_	15	9427	_	_	_		0	0	0	0
Hot water floor heating (only in comb. with option 205) 9)	_	10	674	_	_	_	0	0	0	0	0
Hot water heating	_	40	205	_	_	_	0	0	0	0	0
Ultraheat additional heating for S 3004, electric 220 V	_	2	364	0	_	0	_	_	_	_	_
Ultraheat additional heating for S 5004, electric 220 V	_	2	422	_	_	_	_	0	0	0	0
Air Conditioning											
Pre-wiring for A/C	_	0	172	0	0	0	0	0	0	0	0
Roof A/C		35	8145	0	0	0	0	0	0	0	0
Electrical installation											
Electric Autonomy equipment	_	38	492	0	0	0	0	0	0	0	0
Water supply											
City water connection	_	2	414	0	0	0	0	0	0	0	0
Exterior shower	_	2	396	0	0	0	0	0	0	0	0
Fresh water tank 70 l	_	2.5	592	0	0	0	0	0	0	0	0
Shower equipment with shower fittings and curtain	_	5	1097	0	0	0	0	0	0	0	0
Waste water pipes insulated and heated	_	5	520	0	0	0	0	0	0	0	0
Gas supply											
DuoControl safety gas pressure regulator with crash sensor and EisEx gas regulator heater	_	2.5	784	0	0	0	0	0	0	0	0
Gas socket (exterior)	_	1	187	0	0	0	0	0	0	0	0
Packages											



Optional equipment*	Included in package	Additional weight (kg)*	Code	460 EL	490 EST	510 LE	520 ELT	530 DR	560 FMK	650 RQT	730 FKR
Mover Autonomy Package (single axle)	_	70	5560	0	0	0	0	0	0	_	_
Mover Autonomy Package (tandem axle)	_	98	5561	_	_	_	_	_	_	0	0
Safety Package	_	7	8950	0	0	0	0	0	0	0	0
Shower Package	_	7	6105	0	0	0	0	0	0	0	0
Styling Package silver (single axle)	_	51.1	13255	_	_	_	_	_	0	_	_
Styling Package silver (single axle)	_	48.3	13255	_	0	0	0	0	_	_	_
Styling Package silver (single axle)	_	45.7	13255	0	_	_	_	_	_	_	_
Styling Package silver (tandem axle 2.8 t)	_	47.4	13259	_	_	_	_	_	_	_	0
Styling Package silver (tandem axle)	_	43.4	13257	_	_	_	_	_	_	_	0
Styling Package silver (tandem axle)	_	41.1	13257	_	_	_	_	_	_	0	_
Styling Package white (single axle)	_	45.7	13254	0	_	_	_	_	_	_	_
Styling Package white (single axle)	_	48.3	13254	_	0	0	0	0	_	_	_
Styling Package white (single axle)	_	51.1	13254	_	_	_	_	_	0	_	_
Styling Package white (tandem axle 2.8 t)	_	47.4	13258	_	_	_	_	_	_	_	0
Styling Package white (tandem axle)	_	43.4	13256	_	_	_	_	_	_	_	0
Styling Package white (tandem axle)	_	41.1	13256	_	_	_	_	_	_	0	_
Water & Electric Autonomy Package with Combi or hot water heating system	_	40.5	9943	_	0	_	0	_	_	_	_
Water and Electric Autonomy Package Combi 4	_	55.5	11031	0	_	0	_	_	_	_	_
Water and Electric Autonomy Package Combi 6	_	55.5	11032	_	_	_	_	0	0	0	0
Winter Comfort Package Combi 4	_	50.1	10479	_	_	0	_	_	_	_	_
Winter Comfort Package Combi 4	_	47.6	10479	0	_	_	_	_	_	_	_
Winter Comfort Package Combi 6	_	50.1	9536	_	_	_	_	0	_	0	_
Winter Comfort Package Combi 6	_	55	9536	_	_	_	_	_	_	_	0
Winter Comfort Package Combi 6	_	52.8	9536	_	_	_	_	_	0	_	_
Winter Comfort Package SNOW	_	76.8	5459	_	_	_	_	_	0	_	_
Winter Comfort Package SNOW	_	74.1	5459	_	_	_	0	0	_	0	_
Winter Comfort Package SNOW	_	79	5459	_	_	_	_	_	_	_	0
Winter Comfort Package SNOW PLUS	_	80	5551	_	_	_	_	_	_	_	0
Winter Comfort Package SNOW PLUS	_	77.8	5551	_	_	_	_	_	0	_	_
Winter Comfort Package SNOW PLUS	_	75.1	5551	_	_	_	0	0	_	0	_
Winter Comfort Package for Combi heating	_	35.1	10481	_	0	_	0	_	_	_	_
Miscellaneous											
Registration documents (CoC papers)		0	15151	•	•	•	•	•	•	•	•
2				T.	·	· ·					

O Optional equipment - Not possible lacktriangle Standard equipment lacktriangle Mandatory Δ Not known at the time of publication



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the payload. The specified additional weight for packages and optional equipment shows the additional weight compared with the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the mass for optional equipment specified by the manufacturer in the model overviews. This is an imputed

Beduin Scandinavia

Design, comfort and freedom

Loft-style room concepts with unusual layouts and natural materials create a Scandinavian flair with a touch of luxury. The Dethleffs flagship now makes caravanning possible 365 days a year. The powerful hot water heating and the electric floor heating on board guarantee cosy warmth even at sub-zero temperatures.

Technical info Overall length, approx. 768 - 901 cm Overall width, approx. 230 - 250 cm Overall height, approx. 265 cm Headroom in living area, approx. 198 cm

Maximum values partly not possible for all models or only in connection with certain options.

Upholstery



+ Upholstery Amposta



+ Upholstery Badalona ○



+ Upholstery Tarragona O

Plus factors

- + Upscale standard equipment: with hot-water heating as standard, electr. floor heating, side panels in smooth white sheet metal and a wide range of other options
- + Gourmet holidays made easy: high-quality kitchen equipment with oven/cooker combination and a lot of space for food prep
- + Inviting ambience: indirect lighting and illuminated kitchen back panel ensure special atmosphere
- + Unsurpassed comfort: high-quality padding and cleverly sewn fabrics encourage you to stick around
- + Step in: comfortable entry thanks to extra-wide entrance door with window
- + Watch out winter campers: be prepared for colder temperatures with the optional Winter Comfort Package Premium

Wood décor



+ Wood décor Amberes Oak

O optionally available

























Beduin Scandinavia Technical info









Beduin Scandinavia		540 QMK	550 BET	550 RD	550 SE
Standard chassis		Lightweight chassis, 1800 kg	Lightweight chassis, 1800 kg	Lightweight chassis, 1800 kg	Lightweight chassis, 1800 kg
Overall length, approx.	cm	768	812	806	806
Body length approx.	cm	650	675	675	675
Overall width, approx.	cm	250	230	230	230
Overall height, approx.	cm	265	265	265	265
Circumferential dimension awning approx.	cm	1048	1078	1078	1078
Headroom in living area, approx.	cm	198	198	198	198
Thickness floor / side walls / roof	mm	42 / 34 / 34	42 / 34 / 34	42 / 34 / 34	42 / 34 / 34
Tire size		195 R14C LI106	195 R14C LI106	195 R14C LI106	195 R14C LI106
Bed dimension: Front bed, L x W, approx.	cm	195 x 135		220 x 110	
Bed dimension: Central / middle bed, L X W, approx.	cm	230 x 115	180 x 110		220 x 110
Bed dimension: Rear bed, L x W, approx.	cm	190 x 75 / 190 x 70	205 x 80 / 190 x 80 / 205 - 190 x 215 〇	195 x 150	2x 200 x 85 / 200 x 210
Sleeping berths standard / max.		5	3	3	3
Mass in running order (+/-5%)*	kg	1615 (1534 to 1696)*	1645 (1563 to 1727)*	1600 (1520 to 1680)*	1545 (1468 to 1622)*
Manufacturer-specified mass for optional equipment*	kg	70	58	103	158
Technically permissible maximum laden mass*	kg	1800	1800	1800	1800
Heating		Hot water heating, 6.4 kW Gas-Electric	Hot water heating, 6.4 kW Gas-Electric	Hot water heating, 6.4 kW Gas-Electric	Hot water heating, 6.4 kW Gas-Electric
Refrigerator volume (thereof freezer), approx.	1	137 (15)	137 (15)	137 (15)	137 (15)
Waste water tank, approx.	I	22	22	22	22
Fresh water tank capacity, total/ Fresh water tank capaci driving filling	ty at	53 / 15	53 / 15	53 / 15	53 / 15
Sockets: 12 V / 230 V / USB		0 / 7 / 3	0/7/1	0 / 8 / 1	0/7/1



The specified mass in running order is a standard value defined in the type approval procedure. Due to manufacturing tolerances, the actual weighed mass in running order may deviate from the value stated above. Deviations of up to \pm 5% of the mass in running order are legally permissible and possible. The permissible range in kilograms is stated in parentheses after the mass in running order. The mass for optional equipment specified by the manufacturer is an imputed value determined for each type and layout by which Dethleffs specifies the maximum weight available for factory-fitted optional equipment. The purpose of limiting optional equipment is to ensure that the minimum payload, i.e. the legally required free mass for baggage and retrofitted accessories, is actually available for the load capacity of vehicles delivered by







Beduin Scandinavia		670 BET	690 BQT
Standard chassis		Lightweight chassis, 2200 kg	Lightweight chassis, 2200 kg
Overall length, approx.	cm	872	901
Body length approx.	cm	735	765
Overall width, approx.	cm	250	250
Overall height, approx.	cm	265	265
Circumferential dimension awning approx.	cm	1138	1163
Headroom in living area, approx.	cm	198	198
Thickness floor / side walls / roof	mm	42 / 34 / 34	42 / 34 / 34
Tire size		195/70 R14C LI104	195/70 R14C LI104
Bed dimension: Front bed, L x W, approx.	cm		
Bed dimension: Central / middle bed, L X W, approx.	cm	220 x 110	230 x 115
Bed dimension: Rear bed, L x W, approx.	cm	2x 200 x 85 / 200 x 230 O	185 - 200 x 155
Sleeping berths standard / max.		3	3
Mass in running order (+/-5%)*	kg	1845 (1753 to 1937)*	1870 (1777 to 1964)*
Manufacturer-specified mass for optional equipment*	kg	252	224
Technically permissible maximum laden mass*	kg	2200	2200
Heating		Hot water heating, 6.4 kW Gas-Electric	Hot water heating, 6.4 kW Gas-Electric
Refrigerator volume (thereof freezer), approx.	- 1	156 (29)	156 (29)
Waste water tank, approx.	I	22	22
Fresh water tank capacity, total/ Fresh water tank capacity at driving filling	- 1	53 / 15	53 / 15
Sockets: 12 V / 230 V / USB		0/9/1	0 / 8 / 1

O Optional equipment — Not possible • Standard equipment • Mandatory 🛆 Not known at the time of publication



The specified mass in running order is a standard value defined in the type approval procedure. Due to manufacturing tolerances, the actual weighed mass in running order may deviate from the value stated above. Deviations of up to \pm 5% of the mass in running order are legally permissible and possible. The permissible range in kilograms is stated in parentheses after the mass in running order. The mass for optional equipment specified by the manufacturer is an imputed value determined for each type and layout by which Dethleffs specifies the maximum weight available for factory-fitted optional equipment. The purpose of limiting optional equipment is to ensure that the minimum payload, i.e. the legally required free mass for baggage and retrofitted accessories, is actually available for the load capacity of vehicles delivered by

Ctandard equipment	\succeq					_
Standard equipment	540 QMK	550 BET	550 RD	550 SE	670 BET	690 BQT
Chassis	-		i	i		
Single axle premium wheel 195 R14 C LI106 (with steel wheel 1.700 kg and 1.800 kg)						
Tandem axle premium wheel 195/70 R14 C L1106 (with steel wheel 2.200 kg to 2.800 kg)						
Zinc-plated chassis with inertia braking system with reversing automatic						
Chassis features	_	Ť	Ť	Ť		Ť
AAA self-adjusting brake	•	•		•		
ACS stabiliser	•					
Draw bar cover						
High-quality brand-name tyres, designed for a speed of 100 km/h						
Lightweight corner steadies Octagon shock absorber						
Wheel trims for 14" tyres						
		Ť		Ť	Ť	Ť
Exterior features						
Floor of the gas bottle locker made of rot-resistant and robust corrugated aluminium	•	•				•
Flyscreen door						
Front parts in gas locker area made of LFI (long fiber injection) technology, shock resistant, robust and repair-friendly	•					
Fully-insulated wheel houses	•					
Midi Heki clear-view skylight with blackout blind, flyscreen and integrated lights, operation with crank handle	•	•	•	•		
Opening windows, trapezoid, insulated and double-glazed (graphite grey) with blackout and mosquito blinds						
Panoramic front window	_		_	_		
Robust GRP roof						
Sidewall skirts with integrated side-marker lamps						
Skylight Mini Heki						
Space-saving gas locker door which opens upwards Spare wheel carrier in gas locker						
Storage space for 2 gas bottles with 11 kg filling weight each						
Wide, one-piece habitation door with window						
Exterior design						
Front and rear in smooth sides white						
Manoeuvring handles in chrome design	•	•	•	•		
Smooth sides white	•	•	•			
Access locker doors						
Access locker door front left 997x419 mm	•	_	_	_	_	_
Access locker door rear right side 648x348 mm		_	•	_	_	_
Access locker door rear right side997x419 mm	_	•	-	•		_
Interior design						
Upholstery Amposta	•	•	•	•		•
Wood décor Amberes Oak	•					
Textile equipment						
7-zones double bed mattress, made of heat-regulating material	•	_	•	_	_	•
7-zones mattress left side, made of heat-regulating material	_		_			_
7-zones mattress right side, made of heat-regulating material	_	•	_	•	•	_
Corner head rests for U-shaped seating lounge	•					
High-quality upholstery and materials in the seating group	•	•	•	•	•	•
Furniture layouts						
AirPlus - perfect air circulation in the interior and rear ventilation of the overhead lockers and sideboards						-
Bunk bed with 2 sleeping berths, not foldable		_	_	_		_
Bunk beds with safety net and ladder			_		_	
One-legged telescopic table, height adjustable						
Seating lounge converts to bed	•	•	•	•		•
Special slatted frame with flexible natural rubber holders, opening for optimal use of storage compartments under the beds						
, , , , , , , , , , , , , , , , , , , ,						

Standard equipment 540 QMK 550 BET 550 RD Kitchen Generous drawers with soft closing for absolutely silent closing High-quality three-cooker hob with electric ignition and built-in oven Kitchen worktop with indirect lighting Large fridge with 137 liters capacity and 15 liters freezer compartment Large fridge with 156 liters capacity and 29 liters freezer compartment Oven Practical apothecary drawers (depending on layout) Bathroom Integrated design washbasin made of solid surface material Shower tray Skylight with mosquito net Space-saving fold-away washbasin for easy storage in the bathroom cabinet Multimedia Preparation for flat screen TV (antenna cable and TV bracket) Heating Electric floor heating Hot water heating Air Conditioning Pre-wiring for A/C **Electrical installation** 12 V power supply throughout vehicle Awning light 12V CEE external output socket for 230V on-board electrics Compact power distribution unit with 230V safety device and 12V fuse box in wardrobe incl. powerful 340W transformer Illuminated kitchen back panel Indirect lighting LED light bar system 12V (on head-side of bed and in seating lounge)

USB port for spotlight bar

Water supply
Electric water supply
Fresh water tank 38 I
Mobile 22 I waste water tank

Packages Beduin Scandinavia

Package	Mover Autonomy Package (single axle) (5560)	Mover Autonomy Package (tandem axle) (5561)
Mover manoeuvring support for single-axle	Х	
Electric Autonomy equipment	Х	X
Mover manoeuvring support for tandem-axle		X
Additional weight (kg)*	70	98

Package	Water & Electric Autonomy Package with Combi or hot water heating system (9943)
Electric Autonomy equipment	х
Fresh water tank 70 I	х
Additional weight (kg)*	40.5

Package	Winter Comfort Package Premium (11332)	Winter Comfort Package Premium (11332)	Winter Comfort Package Premium (11332)
Hot water floor heating (only in comb. with option 205)	Х	Х	Х
Heated and insulated 42-litre waste water tank	Х	Х	х
Waste water pipes insulated and heated	Х	Х	х
Electric Autonomy equipment	Х	Х	х
Flush-fitting windows (not possible for front and rear windows)	Х	Х	х
XPS insulation for front, rear and sides (depending on vehicle size)	Х		
XPS insulation for front, rear and sides (depending on vehicle size)		Х	
XPS insulation for front, rear and sides (depending on vehicle size)			Х
Additional weight (kg)*	82.1	84.8	87

Safety Package (8950)

ATC Trailer Control

DuoControl safety gas pressure regulator with crash sensor and EisEx gas regulator heater

Smoke detector

Additional weight (kg)*

doutonal weight (kg)

Shower Package (6105)

Shower equipment with shower fittings and curtain

City water connection

Additional weight (kg)*

 \triangle Not known at the time of publication



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the payload. The specified additional weight for packages and optional equipment shows the additional weight compared with the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the mass for optional equipment specified by the manufacturer in the model overviews. This is an imputed

Optional equipment*	Included in package	Additional weight (kg)*	Code	540 QMK	550 BET	550 RD	550 SE	670 BET	690 BQT
Chassis									
17" alloy wheels in Dethleffs design (single axle)	_	10	11608	0	0	0	0	_	_
17" alloy wheels in Dethleffs design (tandem axle)	_	0	11609	_	_	_	_	0	0
Tyres on alloy wheels 195 R14 C LI106, 1700 kg and 1800 kg	_	2	838	0	0	0	0	_	_
Tyres on alloy wheels 195/70 R14 C LI104, 2200 kg to 2800 kg	_	4	859	_	_	_	-	0	0
Weight upgrade									
Weight upgrade 1.900 kg (incl. alloy wheel 225/70 R15 C LI112)	_	12.4	394	_	0	0	0	_	_
Weight upgrade 1.900 kg (incl. alloy wheel 225/70 R15 C L1112)	_	17.9	394	0	_	_	_	_	_
Weight upgrade 2.000 kg (incl. alloy wheel 225/70 R15 C LI112)	_	17.9	138	0	_	_	_	_	_
Weight upgrade 2.000 kg (incl. alloy wheel 225/70 R15 C LI112)	_	12.4	138	_	0	0	0	_	_
Weight upgrade 2.500 kg (incl. steel wheel 195/70 R14 C L1104)	_	0	496	_	_	_	_	0	0
Chassis features									
ATC Trailer Control	_	4	748	0	0	0	0	0	0
Breakdown kit	_	1	620		•	0	0		
Large support feet, 4 pc.	_	1	6348	0	0	0	0	0	0
Solid rubber support wheel with support load indicator	_	2	10063	0	0	0	0	0	0
Spare tyre with alloy wheel 195 R14 C 8PR-LI 106, 1.700 kg and 1.800 kg	_	19	839	_	0	_	0	_	_
Spare tyre with alloy wheel 225/70 R15 C LI 112 , 1.900 kg and 2.000 kg	_	23.5	1092	_	0	_	0	_	_
Spare tyre with steel wheel 195 R14 C LI 106, 1.700 kg and 1.800 kg	-	19.5	833	_	0	_	0	_	_
Exterior features									
Cassette awning 4500x2500 mm, manual	_	30	6928	0	0	0	0	_	_
Cassette awning 5500x3000 mm, manual	_	50.6	6928	_	_	_	_	0	0
Flush-fitting windows (not possible for front and rear windows) 8)	_	3	7561	0	0	0	0	0	0
Front window		4	982	0	•	•	•	•	•
Rear window	_	4	1108	_	_	0	0	_	_
XPS insulation for front, rear and sides (depending on vehicle size)	_	20.1	179	0	_	_	_	_	_
XPS insulation for front, rear and sides (depending on vehicle size)	_	22.8	179	_	0	0	0	0	_
XPS insulation for front, rear and sides (depending on vehicle size)		25	179	_	_	_	_	_	0
Exterior design									
Front moulding with high attachment and roof rails ¹⁰⁾		1	627	0	0	0	0	0	0
Rear light carrier with high attachment and roof rails 11)	_	11	624	0	0	0	0	0	0
Smooth sides titanium silver metallic		0	659	0	0	0	0	0	0
Access locker doors									
Access locker door front right side 1069x299 mm	_	2	1084	_	_	0	_	_	_
Access locker door rear left side 648x348 mm	_	2	1073	_	_	0	_	_	_
Access locker door rear left side 997x419 mm	_	2.2	1081	_	_	_	0	_	•
Interior design									
Upholstery Badalona	_	0	11330	0	0	0	0	0	0
Upholstery Tarragona	_	0	11331	0	0	0	0	0	0
Textile equipment									
7-zones double bed mattress, made of heat-regulating material with watergel cover	-	4	8214	0	_	0	_	-	0
7-zones mattress left side, made of heat-regulating material with watergel cover	_	2	8215	_	0	_	0	0	_
7-zones mattress right side, made of heat-regulating material with watergel cover	_	5	8216	_	0	_	0	0	_



Optional equipment*	Included in package	Additional weight (kg)*	Code	540 QMK	550 BET	550 RD		670 BET	690 BQT
Loose carpet		8.5	513	0	0	0	0	0	0
Furniture layouts									
Sideboard instead of couch (opposite the central seating group)		0	131		0	_	•	0	0
Single beds convert to double bed	_	5	685	_	0	_		0	_
Slatted bed frame with adjustable head section		1	871		0	_	0	0	_
Interior features									
2 kg fire extinguisher	_	3.5	843	0	0	0	0	0	0
Smoke detector	-	0.5	8949	0	0	0	0	0	0
Kitchen									
Extractor fan	-	3	785	0	_	0	0	-	_
Kitchen worktop extension, foldable	_	1	1107	_	_	0	_	_	_
Multimedia									
FS-SAT system Voyager 65 Digimatic	_	10	1049	_	_	0	0	_	0
Flat screen TV 22" incl. DVD player and receiver	_	3.5	1103	0	0	0	0	0	0
Flat screen TV 32" ¹²⁾	_	5.6	817	_	0	_	_	0	0
Flat screen TV 32" ¹⁴⁾	_	5.6	817	_	_	_	0	_	_
Multifunctional external connection, 12 V, 220 V, TV and SAT	_	1	611	0	0	0	0	0	0
SAT parabol antenna flat 65 Easy 65 Twin	_	14	879	_	_	0	0	_	0
TV lift ¹³⁾	_	5.4	7006	_	0	_	0	0	0
Heating									
Hot water floor heating (only in comb. with option 205) 9)	_	10	674	0	0	0	0	0	0
Air Conditioning									
Roof A/C	_	35	8145	0	0	0	0	0	0
Electrical installation									
Electric Autonomy equipment	_	38	492	0	0	0	0	0	0
Water supply					Ť				
City water connection	_	2	414	0	0	0	0	0	0
Exterior shower	_	2	396			0			0
Fresh water tank 70 l	_	2.5	592	0	0	0	0	0	0
Heated and insulated 42-litre waste water tank ¹⁵⁾	_	6	10067	0	0	0	0	0	0
Shower equipment with shower fittings and curtain	_	5	1097	0	0	0	0	0	0
Waste water pipes insulated and heated	_	5	520	0	0	0	0		0
Gas supply									
DuoControl safety gas pressure regulator with crash sensor and EisEx gas regulator heater	-	2.5	784	0	0	0	0	0	0
Gas socket (exterior)	_	1	187	0	0	0	0	0	0
Packages									
Mover Autonomy Package (single axle)		70	5560	0	0	0	0	_	_
Mover Autonomy Package (tandem axle)	_	98	5561	<u> </u>	_	_	_	0	0
Safety Package	_	7	8950	0	0	0	0	0	0
Shower Package	_	7	6105	0	0	0	0	0	0
Water & Electric Autonomy Package with Combi or hot water heating system	_	40.5	9943	0	0	0	0	0	0
Winter Comfort Package Premium	_	82.1	11332	0	-	_	_	_	_



Optional equipment*	Included in package	Additional weight (kg)*	Code	540 QMK	550 BET	550 RD	550 SE	670 BET	690 BQT
Winter Comfort Package Premium	_	84.8	11332	_	0	0	0	0	_
Winter Comfort Package Premium	_	87	11332	_	_	_	_	_	0
Miscellaneous									
Registration documents (CoC papers)	_	0	15151	•	•	•	•	•	•

O Optional equipment lacktriangle Not possible lacktriangle Standard equipment lacktriangle Mandatory Δ Not known at the time of publication



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the payload. The specified additional weight for packages and optional equipment shows the additional weight compared with the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the mass for optional equipment specified by the manufacturer in the model overviews. This is an imputed

value determined for each model and layout that Dethleffs uses to determine the maximum weight available for factory-installed optional equipment. In the event of an increase of load capacity, the mass for optional equipment specified by the manufacturer is increased. For detailed information and explanations on the topic of weight, please refer to the "Legal notes" section.

LEGAL NOTES ON WEIGHT-RELATED INFORMATION

The weight specifications and tests for caravans are regulated uniformly throughout the EU in EU Implementing Regulation No. 2021/535 (until June 2022: EU Regulation No. 1230/2012). We have summarized and explained the essential terminology and legal requirements from this regulation for you below. Our dealers and the Dethleffs configurator on our website are there to give you additional assistance in configuring your vehicle.

1. Technically permissible maximum laden mass

The technically permissible maximum laden mass of the vehicle (e.g. 2,000 kg) is a mass specification defined by the manufacturer that the vehicle must not exceed. You can find information on the technically permissible maximum laden mass of the model you have selected in the technical data. Driving the vehicle even if it exceeds the technically permissible maximum laden mass constitutes an administrative offense that may result in a fine.

2. Mass in running order

In simple terms, the mass in running order is the basic vehicle with standard equipment. This essentially includes the following items:

- the unladen weight of the vehicle together with the bodywork, including operating fluids;
- the standard equipment, i.e. all equipment and standard fittings included when the vehicle leaves the factory;
- the 100% filled water tank or driving tank according to the manufacturer's specifications and a 100% filled aluminum gas cylinder.

You can find information on the mass in running order for each model in our sales documents. It is **important to note** that the value specified in the sales documents for the mass in running order is a **standard value** determined in the type approval process and verified by the authorities. It is legally permissible and possible for the mass in running order of the vehicle delivered to you to deviate from the nominal value specified in the sales documents. The **legally permissible tolerance** is \pm 5%. This allows EU legislation to account for the occurrence of certain fluctuations in the mass in running order due to weight fluctuations in components supplied by third-party suppliers as well as process and weather-related factors.

These weight deviations can be illustrated using the following example calculation:

- Mass in running order according to sales documents: 1,600 kg
- Legally permissible tolerance of \pm 5%: 80 kg
- Legally permissible range of mass in running order: 1,520 kg to 1,680 kg The specific range of permissible weight deviations can be found in the technical data for each model.

Dethleffs makes great efforts to reduce weight variations to the minimum level that is unavoidable for production reasons. Deviations at the upper and lower ends of the range are therefore very rare; however, they cannot be completely ruled out technically, even after carrying out all possible optimization measures. For this reason, Dethleffs checks the actual weight of the vehicle and compliance with the permissible tolerance by weighing each vehicle at the end of the line.

3. Optional equipment and actual mass

According to the legal definition, optional equipment (also including special or additional equipment) includes all optional equipment parts not included with the standard equipment that are fitted to the vehicle under the responsibility of the manufacturer – i.e. at the factory – and can be ordered by the customer (e.g. awning, smooth panel, Alde heating system, oven, etc.). For information on the individual or package weights of the optional equipment that can be ordered, please refer to our sales documents. In this meaning, optional equipment does not include other accessories that are retrofitted by you or your dealer personally after the vehicle has been delivered from the factory.

The mass of the vehicle in running order (see no. 2 above) and the mass of the optional equipment installed on a specific vehicle at the factory are together referred to as the actual mass. You will find the corresponding information for your vehicle after handover under item 13.2 of the Certificate of Conformity (CoC). Please note that this information also represents a standardized value. Since the mass in running order – as an element of the actual mass – is subject to a legally permissible tolerance of \pm 5% (see no. 2), the actual mass may also deviate accordingly from the specified nominal value.

4. Payload and minimum payload

The installation of **optional equipment** is also subject to technical and legal limits: It is only permissible to order an amount of optional equipment for installation at the factory that will leave sufficient free weight for baggage and other accessories (i.e. "payload") without exceeding the technically permissible maximum laden mass.

The payload is obtained by deducting the mass in running order (nominal value according to sales documents; see no. 2 above) and the mass of the optional equipment from the technically permissible maximum laden mass (see no. 1 above). The EU regulations stipulate a fixed minimum payload for caravans that must remain as a minimum for baggage or other accessories not installed at the factory. This minimum payload is calculated as follows:

Minimum payload in kg \geq 10 * (n + L) where "n" = maximum number of sleeping berths and "L" = total length of the vehicle body (without drawbar).

The maximum number of sleeping berths corresponds to the actual configured sleeping berths of the individual vehicle. For a caravan with 6 designated sleeping berths and a total length of the vehicle body of 7 m, the minimum payload is calculated as follows: 10 kg * (6 + 7) = 130 kg.

To ensure that the minimum payload is maintained, there is a maximum combination of optional equipment that can be ordered for each vehicle model. In the above example with a minimum payload of 130 kg, the total mass of the optional equipment for a vehicle with 6 designated sleeping berths and a mass in running order of 1,750 kg should not exceed 120 kg:

2,000 kg technically permissible maximum laden mass

- 1,750 kg mass in running order
- 130 kg minimum payload
- = 120 kg maximum permissible mass for optional equipment

It is important to note that this calculation is based on the standard value for the mass in running order specified in the type approval procedure and does not account for permissible weight deviations for the mass in running order (see no. 2 above). If the maximum permissible value of 120 kg for the optional equipment is nearly or fully exhausted in this example and the standard value of the mass in running order is applied, it is possible for the minimum payload of 130 kg to be complied with mathematically in the event of an upward weight deviation even if the vehicle has no load capacity.

Here is another example calculation for a vehicle with 6 sleeping berths whose actual weighed mass in running order is 2% above the nominal value:

2,000 kg technically permissible maximum laden mass

- 1,785 kg actual weighed mass in running order
 (in the example: 2% higher than the specified value of 1,750 kg)
- 120 kg optional equipment (maximum permissible value)
- = 95 kg actual load capacity (< minimum pay-mass of 130 kg)

To avoid such a situation, Dethleffs further reduces the maximum permissible weight of the total optional equipment that can be ordered depending on the specific model. The limitation of optional equipment is intended to ensure that the minimum payload, i.e. the legally prescribed free mass for baggage and retrofitted accessories, is actually available for the load capacity of the vehicles delivered by Dethleffs.

Since the weight of a specific vehicle can only be determined when it is weighed at the end of the line, in very rare cases a situation may arise in which the minimum payload is not guaranteed at the end of the line despite this limitation of optional equipment. In order to guarantee the minimum payload even in these cases, Dethleffs will check together with your trading partner and you before delivery of the vehicle whether, for example, the load capacity of your vehicle is to be increased or optional equipment removed.

5. Effects of tolerances of the mass in running order on the remaining load capac

Irrespective of the minimum payload, you should bear in mind that unavoidable production-related fluctuations in the mass in running order – both upwards and downwards – have a corresponding effect on the remaining load capacity: If, for example, you order our example vehicle with optional equipment with a total weight of 90 kg, the calculated payload based on the standard value for the mass in running order is 160 kg.

The load capacity actually available may deviate upwards or downwards from this value due to tolerances. If the mass of your vehicle in running order is approximately 2% higher than specified in the sales documents, the load capacity is reduced from 160 kg to 125 kg:

2,000 kg technically permissible maximum laden mass

- 1,785 kg actual weighed mass in running order (in the example: 2% higher than the specified value of 1,750 kg)
- 90 kg ordered optional equipment of the specific vehicle
- 125 kg actual load capacity

In order to ensure that the calculated payload is actually adhered to, you should therefore take the possible and permissible tolerances for the mass in running order into account as a precaution when configuring your vehicle.

We also recommend weighing the loaded caravan on a scale before each journey to check whether the technically permissible total weight is adhered to. In addition, we recommend checking the actual drawbar load of the loaded vehicle. This must not be higher than the max. drawbar load of the towing vehicle. Furthermore, the technically permissible maximum laden mass of the vehicle combination must be observed when loaded, i.e. the maximum mass of the combination of your motor vehicle and your caravan.

TECHNICAL INFORMATION / FOOTNOTES

If you order your vehicle with additional equipment, you should check whether it makes sense or is necessary to increase the vehicle's weight! The optional equipment partially replaces the standard equipment.

FOOTNOTES

- 1) With the Dynamic Package, the vehicle must be approved for speeds of 100 km/h.
- 2) Only in combination with package #9243 "Touring Package c'joy".
- 3) Only in combination with option #8699 "Hanging table with rotating device"
- 4) Only in combination with option #187 "Gas exterior socket"
- 5) Only in combination with option #611 "Multifunction exterior socket 12V, 220V, TV and SAT"
- 6) Only in combination with package #7345 "Touring Package c'go".
- 7) Not in combination with option #200 "Bunk beds with 3 sleeping berths".
- 8) Not available for front or rear windows. These windows are standard design.
- 9) Only in combination with option #205 "Hot water heating".
- 10) Only in combination with option #624 "Rear light carrier with high attachment and roof rails".
- 11) Only in combination with option #627 "Front with high attachment and roof rails".
- 12) Price incl. options #131 and #7006.
- 13) Only in combination with option #131 "Sideboard instead of sofa (opposite to central seating group)".
- 14) Price incl. option #7006
- 15) Only in combination with option #520 "Waste water hoses insulated and heated".

General Information

The information on the scope of delivery, appearance, performance, dimensions and weights of the vehicles correspond to the knowledge available at the time of going to press and to the European homologation regulations.

Technical changes in design and equipment as well as errors excepted. This Technical Information 03/2024 is valid as of February 1st, 2024.

Vehicle illustrations in this document may contain optional extras subject to surcharge. We expressly reserve the right to make changes. With the publication of this document, all previous Technical Information become invalid.

Different Euro prices may apply throughout Europe. This is due to different country-specific standard equipment and different VAT or luxury tax rates.

